

AD-A133720

AFAMRL-TR-83-058



**DEVELOPMENT OF AN INTERACTIVE COMPUTER
PROGRAM TO PRODUCE BODY DESCRIPTION DATA**

L. DOUGLAS BAUGHMAN

*UNIVERSITY OF DAYTON
RESEARCH INSTITUTE
300 COLLEGE PARK AVENUE
DAYTON, OHIO 45469*

JULY 1983

Approved for public release; distribution unlimited.

DTIC FILE COPY

AIR FORCE AEROSPACE MEDICAL RESEARCH LABORATORY
AEROSPACE MEDICAL DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433

DTIC
ELECTE
OCT 18 1983
S D D

NOTICES

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Please do not request copies of this report from Air Force Aerospace Medical Research Laboratory. Additional copies may be purchased from:

National Technical Information Service
5285 Port Royal Road
Springfield, Virginia 22161

Federal Government agencies and their contractors registered with Defense Technical Information Center should direct requests for copies of this report to:

Defense Technical Information Center
Cameron Station
Alexandria, Virginia 22314

TECHNICAL REVIEW AND APPROVAL

AFAMRL-TR-83-058

This report has been reviewed by the Office of Public Affairs (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER



HENNING E. VON GIERKE, Dr Ing

Director
Biodynamics and Bioengineering Division
Air Force Aerospace Medical Research Laboratory

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFAMRL-TR-83-058	2. GOVT ACCESSION NO. AD-4133 720	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) DEVELOPMENT OF AN INTERACTIVE COMPUTER PROGRAM TO PRODUCE BODY DESCRIPTION DATA		5. TYPE OF REPORT & PERIOD COVERED Technical Report April 1982 - August 1982
		6. PERFORMING ORG. REPORT NUMBER UDP-TR-83-06
7. AUTHOR(s) L. Douglas Baughman		8. CONTRACT OR GRANT NUMBER(s) F33615-81-C-0513
9. PERFORMING ORGANIZATION NAME AND ADDRESS University of Dayton Research Institute 300 College Park Avenue Dayton, Ohio 45469		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62202F, 7231-13-16
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Aerospace Medical Research Laboratory, Aerospace Medical Division, Air Force Systems Command, Wright-Patterson AFB, Ohio 45433		12. REPORT DATE July 1983
		13. NUMBER OF PAGES 74
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release, distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES AFAMRL Contact: Mark M. Hoffman, AFAMRL/BBM, 513/255-3667		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Anthropometry Body Description Data Body Dynamics Crash Simulation Inertial Properties		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report documents program GEBOD (Generator of BODY data) an interactive computer program which produces the body description portion of the ATB (Articulated Total Body) Model input deck. The ATB Model simulates the motion and dynamic properties of the human body during events such as aircraft flight seat ejection and automobile crashes. This simulation requires the mass, center of gravity location, contact surface dimensions, joint locations, principal moments		

DD FORM 1 JAN 73 1473

SUMMARY

Program GEBOD was developed in order to automate production of the body description portion of the ATB Model input deck. The ATB Model simulates the motion of the human body during dynamic events such as automobile crashes and aircraft cockpit ejections. It requires mass, center of gravity location, contact surface dimensions, principal moments of inertia and their associated directions for each of 15 body segments. Additionally, the ATB Model requires data locating the 14 joints that connect the body segments for body description.

The starting point for program GEBOD was a program written by Calspan Corporation named program GOOD, which was also designed to produce body description data for crash simulation models. A series of modifications and improvements to program GOOD resulted in program GEBOD. This report details those modifications and improvements.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



PREFACE

Work described in this report was performed by the University of Dayton Research Institute (UDRI) under Contract No. F33615-81-C-0513. Principal investigator for UDRI was Mr. L. Douglas Baughman. Sponsor of the contract was the Modeling and Analysis Branch of the Air Force Aerospace Medical Research Laboratory (AFAMRL/BBM). Dr. Ints Kaleps (Chief, AFAMRL/BBM) acted as technical advisor for the work described in this report. The author would like to thank Mrs. Charlene Dunson of UDRI for her careful typing of this report.

TABLE OF CONTENTS

Section	Page
1 INTRODUCTION	7
2 BODY DIMENSION SET	10
3 BODY GEOMETRY	13
3.1 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF TORSO SEGMENTS	15
3.2 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF THE HEAD AND NECK	20
3.3 DETERMINING EXPRESSIONS FOR ANKLE LOCATIONS RELATIVE TO THE FEET	20
3.4 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF LIMB SEGMENTS	21
3.5 CONCLUSION	21
4 INERTIAL PROPERTIES OF BODY SEGMENTS	23
APPENDIX A: USER'S GUIDE	27
APPENDIX B: SAMPLE OUTPUT FROM PROGRAM GEBOD	31
APPENDIX C: COMPARISON OF REGRESSION TO PERCENTILE BASIS FOR BODY DIMENSIONS	33
APPENDIX D: BODY DIMENSION REGRESSION EQUATIONS DEVELOPED FOR GEBOD	36
APPENDIX E: INERTIAL PROPERTIES OF ELLIPSOIDS AND RIGHT ELLIPTICAL CYLINDER STACKS	49
APPENDIX F: SOURCE LISTING OF PROGRAM GEBOD	52
REFERENCES	69

LIST OF FIGURES

Figure		Page
1	Fifteen Segment Configuration Commonly Used With Articulated Total Body (ATB) Model.	9
2	Local Reference Axis Systems and Joint Locations Used by GEBOD to Prepare Input Data for the ATB Model.	14
3	Spherical Joint Concept Developed for Program GOOD and Used to Determine Joint Locations Relative to Limb Segments.	22
4	Cross Sections of Right Elliptical Solids Used to Approximate Segment Inertial Properties.	25

LIST OF TABLES

1	CORRESPONDENCE BETWEEN 32 BODY DIMENSIONS USED AND THEIR SOURCES	11
2	JOINT LOCATIONS RELATIVE TO LOCAL REFERENCE AXIS SYSTEMS	16
3	CONTACT ELLIPSOID SEMIAXES	18

GLOSSARY OF TERMS

- Anthropometry: The study of human body dimensions.
- Axilla: The arm pit.
- Iliocristale: The most superior point on the rim of the pelvic bone.
- Inertial Properties: The mass, center of gravity location, principal moments of inertia and associated directions of a body.
- Numerical Integration: Approximating the value of an integral by arithmetic computations.
- Tenth Rib: The lowest palapable rib in the mid-axillary line.

GLOSSARY OF TERMS

- Anthropometry: The study of human body dimensions.
- Axilla: The arm pit.
- Iliocristale: The most superior point on the rim of the pelvic bone.
- Inertial Properties: The mass, center of gravity location, principal moments of inertia and associated directions of a body.
- Numerical Integration: Approximating the value of an integral by arithmetic computations.
- Tenth Rib: The lowest palapable rib in the mid-axillary line.

LIST OF ABBREVIATIONS, ACRONYMS, AND SYMBOLS

- AFAMRL/BBM - Modeling and Analysis Branch of the Air Force Aerospace Research Laboratory.
- ATB Model - Articulated Total Body Model.
- CVS - Crash Victim Simulator.
- DD_i - The i^{th} measurement of the set of 32 body measurements used by both program GEBOD and program.
- GOOD - Generator Of Occupant Data.
- GEBOD - Generator Of Body Data.
- ROS - Revised Occupant Simulator.
- UDRI - University of Dayton Research Institute.

SECTION 1

INTRODUCTION

The development of mathematical/computer models capable of predicting the motion of the human body in a dynamic environment has created a need for extensive data describing human geometry and inertial properties. These models have been used to predict body motion during events such as automobile crashes and aircraft cockpit ejections and are capable of pointing out potentially hazardous designs for these two environments. Various methods have been utilized to obtain the required body description data: predominantly the use of cadavers (eg., Chandler, et al., 1975 and Walker et al., 1973) and mathematically constructing geometric models of the human body (eg., Hanavan, 1964).


Calspan Corporation developed Program GOOD (Generator Of Occupant Data, Bartz and Gianotti, 1973) in order to automate the production of input data sets for the Crash Victim Simulator (CVS) Program (Bartz, 1971, also Fleck et al., 1975), and the Revised Occupant Simulator (ROS) Model (Segal, 1971). Both of these are computer programs developed by Calspan for the simulation of occupant dynamics during automobile crashes, the ROS Model in two dimensions, and the CVS Program in three-dimensions. The Articulated Total Body (ATB) Model (Fleck and Butler, 1975, also Butler and Fleck, 1980) was developed from the CVS Program, by incorporating modifications to provide the additional capabilities needed to simulate the various aspects of aircraft cockpit ejections. These modifications were performed by Calspan Corporation under the sponsorship of the Modeling and Analysis Branch of the Air Force Aerospace Medical Research Laboratory (AFAMRL/BBM), and were incorporated into the previous CVS Program as user available options.

The ATB Model performs simulations by viewing the human body as a series of connected rigid bodies, each referred to as a body segment. The ATB Model is flexible as to how many segments are used in modeling the human body. The standard configuration, presently being

used, consists of 15 segments, which is illustrated in Figure 1. For each of these body segments the ATB Model requires segment mass, principal moments of inertia, and semiaxes of an ellipsoid approximating the shape of the body segment. Also required are the locations of joints connecting the body segments.

The subject of this report is the development of an interactive computer program which will produce data sets for the ATB Model corresponding to specific types and sizes of human beings. This program has been named GEBOD (Generator of Body Data) and is an extensively modified version of Calspan's Program GOOD, with modifications being done by the University of Dayton Research Institute (UDRI). The changes made to Program GOOD in the development of GEBOD include the following:

1. an interactive format for the input of parameters describing the subject for which body description data is to be produced
2. body dimensions are obtained from regression equations instead of using a fixed percentile (see Appendix C)
3. restructuring the torso segments (thorax, abdomen, and pelvis)
4. development of a new technique for determining inertial properties of the torso and the feet segments
5. the units used for handling of data within the program were changed and allowance was made for results to be output in either metric or English units
6. format changes of the output making it compatible with the most recent version of the ATB Model.



1. Head
2. Neck
3. Thorax
4. Abdomen
5. Pelvis
6. Right Upper Arm
7. Right Lower Arm
8. Left Upper Arm
9. Left Lower Arm
10. Right Thigh
11. Right Calf
12. Right Foot
13. Left Thigh
14. Left Calf
15. Left Foot

Figure 1. Fifteen Segment Configuration Commonly Used With Articulated Total Body (ATB) Model.

SECTION 2

BODY DIMENSION SET

All the computations performed by Program GOOD are based on a set of 32 body measurements. These are used to determine sizes of body segments and the location of joints connecting them. GEBOD also uses this set of body measurements, which is listed in Table 1. Through the remainder of this report references to the i^{th} body measurement will be made as DD_i .

GEBOD has two ways of obtaining values for the required 32 body measurements. These measurements can either be read in from a disk file placed on the computer system by a user of GEBOD, or they can be generated by GEBOD using regression equations. There are three groups of regression equations stored within GEBOD. These groups correspond to possible subject types: adult male, adult female, or child. Within each group there are regression equations for each of the 32 body measurements. Both the adult male and the adult female groups contain three regression equations for each body measurement: one against height, one against weight, and the third a stepwise multiple regression equation against both height and weight. The child group contains four regression equations per body measurement: one against height, one against weight, one against age, and the fourth a stepwise multiple regression against height, weight and age. These different regression equations were developed to provide the user a flexible means for generating data sets.

All of the regression equations stored in GEBOD were computed from data in the AFAMRL Anthropometric Data Bank. A survey containing data on 2,420 male flying personnel of the U.S. Air Force (Grunhofer and Kroh, 1975) was used in the development of the adult male regression equations. For the adult female regressions a survey consisting of data on 1,905 women in the U.S. Air Force (Clauser, et al., 1972) was utilized. The child regression equations were computed from survey consisting of data on 3,782 children aged two to twenty years,

TABLE 1
CORRESPONDENCE BETWEEN 32 BODY DIMENSION USED AND THEIR SOURCES

<u>i</u>	<u>DIMENSION NAME</u>	<u>CHILDREN'S POPULATION</u>	<u>ADULT FEMALE POPULATION</u>	<u>ADULT MALE POPULATION</u>
-1	Age	L ₁₀₁	--	--
0	Weight	L ₁	L ₂	L ₂
1	Standing Height	L ₂	L ₇	L ₁₃
2	Shoulder Height	L ₆₁	L ₁₀	L ₁₅
3	Armpit Height	L ₆₂	L ₁₀ - L ₅₃ /π	L ₁₅ - L ₁₀₃ /π
4	Waist Height	L ₆₉	L ₁₃	L ₂₁
5	Seated Height	L ₉	L ₂₃	L ₃₂
6	Head Length	L ₂₀	L ₉₆	L ₁₅₀
7	Head Breadth	L ₁₉	L ₉₇	L ₁₅₆
8	Head to Chin Height	L ₂₅	L ₁₀₄	L ₁₇₉
9	Neck Circumference	L ₃₂	L ₃₆	L ₆₆
10	Shoulder Breadth	L ₃₆	L ₆₃	L ₅₀
11	Chest Depth	SEMI(L ₆₄ , L ₆₃)	L ₇₄	L ₆₂
12	Chest Breadth	L ₆₄	L ₆₅	L ₅₂
13	Waist Depth	SEMI(L ₆₇ , L ₆₆)	L ₇₅	L ₆₃
14	Waist Breadth	L ₆₇	L ₆₇	L ₅₃
15	Buttock Depth	SEMI(L ₇₂ , L ₇₁)	L ₇₇	L ₆₄
16	Hip Breadth, Standing	L ₇₂	L ₆₈	L ₅₅
17	Shoulder to Elbow Length	L ₃₇	L ₃₁	L ₄₂
18	Forearm-Hand Length	L ₄₁	L ₃₂ + L ₉₁	L ₄₄ + L ₁₇ - L ₁₈
19	Biceps Circumference	L ₃₉	L ₅₅	(L ₁₀₄ + L ₁₀₅ + L ₁₀₆ + L ₁₀₇)/4
20	Elbow Circumference	L ₄₃	L ₅₉	L ₁₀₉
21	Forearm Circumference	L ₄₃	L ₆₀	L ₁₁₀
22	Wrist Circumference	L ₄₅	L ₆₂	L ₁₁₂
23	Knee Height, Seated	L ₁₅	L ₁₈ + L ₄₆ /(2π)	L ₃₇
24	Thigh Circumference	L ₇₇	L ₄₅	L ₉₆
25	Upper Leg Circumference	(L ₇₇ + L ₈₁)/2	(L ₄₅ + L ₄₆)/2	L ₉₈
26	Knee Circumference	(L ₇₇ + L ₈₁)/2	L ₄₆	L ₉₉
27	Calf Circumference	L ₈₁	L ₄₇	L ₁₀₀
28	Ankle Circumference	L ₈₃	L ₄₉	L ₁₀₂
29	Ankle Height, Outside	L ₈₅	L ₂₁	L ₃₁
30	Foot Breadth	L ₈₇	L ₉₅	L ₁₂₇
31	Foot Length	L ₈₆	L ₉₄	L ₁₂₅

NOTE:

- 1) L_i refers to the ith dimension of the appropriate anthropometric survey.
- 2) SEMI(a, b) is a function returning one axis length of an ellipse where b is the circumference of the ellipse, and a is its other axis length.

from throughout the United States (Synder, et al., 1977). In the case of the child regression equations, some of the regressions were based on data pertaining to only a subset of the total population.

None of the three anthropometric surveys used included all of the measurements needed. In those cases where a needed measurement was missing from a survey it was approximated from available measurements. Table 1 lists the measurements actually used from each survey and indicates any approximations made. Appendix D gives a complete listing of the regression equations computed.

SECTION 3


BODY GEOMETRY

The structure and appearance of the human model as depicted by the ATB Model is determined from contact ellipsoid semiaxes and joint locations. A contact ellipsoid is associated with each body segment, giving the segment shape and providing an interaction surface between the segment and its environment. The joints connect segments and serve as pivot points about which rotational motion is allowed.

A joint is located relative to the two segments it connects (see Table 2). For example, the elbow joint is located by two sets of three-dimensional coordinates: one set relative to the local reference system of the upper arm; the other relative to the local reference system of the forearm. Local reference systems (also referred to as segment geometric axis systems) are located at each segment's center of mass with an arbitrary orientation. The orientation of each of these axis systems, relative to the geometry of its segment, may be chosen so as to provide maximum convenience in inputting data items to the ATB Model.

Each local reference axis system is fixed within its segment, and thus changes orientation as the orientation of its segment is changed. For use with GEBOD the local reference axis systems have been chosen so that they all have a common orientation when the model is in an erect standing position, arms extended downward, and toes pointed straight down. When the segments are positioned as described the X axis of each local reference system points forward, each Y to the right, and each Z downward, all relative to the model (see Figure 2).

GEBOD computes joint locations by use of the expressions listed in Table 2. These expressions were developed by using the geometric center of each segment (the geometric center of a segment is the center of that segment's contact ellipsoid) as an approximation for its



LEGEND:

LOCAL REFERENCE SYSTEM ORIGINS

- 1 - PELVIS
- 2 - ABDOMEN
- 3 - THORAX
- 4 - NECK
- 5 - HEAD
- 6 - RIGHT THIGH
- 7 - RIGHT CALF
- 8 - RIGHT FOOT

- 9 - LEFT THIGH
- A - LEFT CALF
- B - LEFT FOOT
- C - RIGHT UPPER ARM
- D - RIGHT FORE ARM
- E - LEFT UPPER ARM
- F - LEFT FORE ARM

JOINTS

- M - ABDOMEN-PELVIS
- N - THORAX-ABDOMEN
- O - NECK-THORAX
- P - HEAD-NECK
- Q - RIGHT HIP
- R - RIGHT KNEE
- S - RIGHT ANKLE
- T - LEFT HIP
- U - LEFT KNEE
- V - LEFT ANKLE
- W - RIGHT SHOULDER
- X - RIGHT ELBOW
- Y - LEFT SHOULDER
- Z - LEFT ELBOW

NOTES:

1. EXCEPT IN THE CASE OF THE FEET THE LOCAL REFERENCE AXES ARE LABELED AS FOLLOWS:
 - A. ALL VERTICAL AXES ARE Z AXES
 - B. ALL HORIZONTAL AXES IN THE FRONT VIEW ARE Y AXES
 - C. ALL HORIZONTAL AXES IN THE RIGHT SIDE VIEW ARE X AXES
2. IN THE CASE OF THE FEET THE LOCAL REFERENCE AXES ARE LABELED AS FOLLOWS:
 - A. ALL VERTICAL AXES ARE X AXES
 - B. BOTH HORIZONTAL AXES IN THE FRONT VIEW ARE Y AXES
 - C. THE HORIZONTAL AXIS IN THE RIGHT SIDE VIEW IS THE Z AXIS
3. IN THE RIGHT SIDE VIEW ONLY LIMB SEGMENTS ON THE RIGHT SIDE OF THE BODY ARE SHOWN

Figure 2. Local Reference Axis Systems and Joint Locations Used By GEBOD to Prepare Input Data for the ATB Model.

center of gravity. Joint coordinates computed using these expressions, then, are not actually relative to segment local reference systems, but to a parallel set of axes located at the geometric center. Once GEBOD has computed the true location of the segment centers of gravity, the appropriate translation is applied to convert to the true local reference systems.

Relative to the segment axis systems described it has been possible to make certain assumptions, simplifying the development of the expressions for joint locations listed in Table 2. First, the X coordinate of all joints relative to appropriate local reference systems, with the exception of the ankles relative to the feet, are zero. Secondly, it is assumed that the only joints with non-zero Y local reference coordinates are the shoulders relative to the thorax and the hips relative to the pelvis (see Figure 2).

Using all the assumptions mentioned the expressions for joint locations as functions of body dimensions were developed, and are listed in Table 2. Similarly, expressions for contact ellipsoid semi-axes are listed in Table 3. Many of these expressions are very straightforward and in many cases have been taken directly from Program GOOD. Others, however, are more complicated and require further explanation.

3.1 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF TORSO SEGMENTS

The way in which the torso is divided into three segments is somewhat arbitrary and has varied over the time that the CVS Program and the ATB Model have been in existence. Program GOOD produces data describing an upper torso that only extends down to the axilla area, with the mid torso then extending from the axilla down to the waist. Present usage of the ATB model defines the mid torso or abdomen as extending from the tenth rib landmark to the iliac crest landmark, with the thorax being all of the torso above, and the pelvis being all of the torso below. Because of this change in the definition of torso segments, joint locations and semi-axes lengths were changed from those given by Program GOOD for the torso.

TABLE 2
JOINT LOCATIONS RELATIVE TO LOCAL REFERENCE AXIS SYSTEMS

<u>JOINT</u>	<u>RELATIVE TO</u>	<u>X</u>	<u>Y</u>	<u>LOCATION</u>	<u>Z</u>
Abdomen pelvis	pelvis	0.0	0.0	$(DD_1 - DD_5 - DD_4 + 0.1(DD_2 - DD_4))/2$	
	abdomen	0.0	0.0	$(DD_2 - DD_4)/10$	
Thorax-abdomen	abdomen	0.0	0.0	$-(DD_2 - DD_4)/10$	
	thorax	0.0	0.0	$9(DD_2 - DD_4)/20$	
Neck-thorax	thorax	0.0	0.0	$-9(DD_2 - DD_4)/20$	
	neck	0.0	0.0	$(DD_1 - DD_8 - DD_2 - \frac{DD_9}{2\pi})/2$	
Head-neck	neck	0.0	0.0	$-(DD_1 - DD_8 - DD_2 - \frac{DD_9}{2\pi})/2$	
	head	0.0	0.0	$(DD_8 + \frac{DD_9}{2\pi})/2$	
Right hip	pelvis	0.0	$(DD_{16} - \frac{DD_{24}}{\pi})/2$	$(DD_4 - (DD_2 - DD_4)/10 - DD_1 + DD_5 - \frac{DD_{24}}{\pi})/2$	
	right thigh	0.0	0.0	$-(DD_1 - DD_5 - DD_{23} + \frac{DD_{26}}{\pi})/2$	
Right knee	right thigh	0.0	0.0	$(DD_1 - DD_5 - DD_{23} + \frac{DD_{24}}{\pi})/2$	
	right calf	0.0	0.0	$-(DD_{23} - DD_{29} + \frac{DD_{28}}{2\pi} - \frac{DD_{26}}{\pi})/2$	
Right ankle	right calf	0.0	0.0	$(DD_{23} - DD_{29} - \frac{DD_{28}}{2\pi})/2$	
	right foot	$\frac{DD_{29}}{2}$	0.0	$-(DD_{31} - \frac{DD_{28}}{\pi})/2$	
Left hip	pelvis	0.0	$-(DD_{16} - \frac{DD_{24}}{\pi})/2$	$(DD_4 - (DD_2 - DD_4)/10 - DD_1 + DD_5 - \frac{DD_{24}}{\pi})/2$	
	left thigh	0.0	0.0	$-(DD_1 - DD_5 - DD_{23} + \frac{DD_{26}}{\pi})/2$	
Left knee	left thigh	0.0	0.0	$(DD_1 - DD_5 - DD_{23} + \frac{DD_{24}}{\pi})/2$	
	left calf	0.0	0.0	$-(DD_{23} - DD_{29} + \frac{DD_{28}}{2\pi} - \frac{DD_{26}}{\pi})/2$	
Left ankle	left calf	0.0	0.0	$(DD_{23} - DD_{29} - \frac{DD_{28}}{2\pi})/2$	
	left foot	$\frac{DD_{29}}{2}$	0.0	$-(DD_{31} - \frac{DD_{28}}{\pi})/2$	
Right shoulder	thorax	0.0	$(DD_{10} - \frac{DD_{19}}{\pi})/2$	$-(DD_2 - DD_3 - \frac{DD_{19}}{2\pi})$	
	right upper arm	0.0	0.0	$-(DD_{17} - \frac{DD_{19}}{\pi})/2$	
Right elbow	right upper arm	0.0	0.0	$(DD_{17} - \frac{DD_{20}}{\pi})/2$	
	right forearm	0.0	0.0	$-(DD_{18} - \frac{DD_{20}}{\pi})/2$	

TABLE 2 (Continued)

Left shoulder	thorax	0.0	$-(DD_{10} - \frac{DD_{19}}{\pi})/2$	$-(DD_2 - DD_3 - \frac{DD_{19}}{2\pi})$
	left upper arm	0.0	0.0	$-(DD_{17} - \frac{DD_{19}}{\pi})/2$
Left elbow	left upper arm	0.0	0.0	$(DD_{17} - \frac{DD_{20}}{\pi})/2$
	left forearm	0.0	0.0	$-(DD_{18} - \frac{DD_{20}}{\pi})/2$

TABLE 3
CONTACT ELLIPSOID SEMIAXES

<u>SEGMENT</u>	<u>X SEMIAXIS</u>	<u>Y SEMIAXIS</u>	<u>Z SEMIAXIS</u>
Pelvis	$\frac{DD_{15}}{2}$	$\frac{DD_{16}}{2}$	$(DD_4 + DD_5 - DD_1 - 0.1(DD_2 - DD_4))/2$
Abdomen	$\frac{DD_{13}}{2}$	$\frac{DD_{14}}{2}$	$(DD_2 - DD_4)/10 + \frac{DD_9}{\pi}$
Thorax	$\frac{DD_{11}}{2}$	$\frac{DD_{12}}{2}$	$.45(DD_2 - DD_4)$
Neck	$\frac{DD_9}{2\pi}$	$\frac{DD_9}{2\pi}$	$(DD_1 - DD_8 - DD_2 + \frac{DD_9}{2\pi})/2$
Head	$\frac{DD_6}{2}$	$\frac{DD_7}{2}$	$(DD_8 + \frac{DD_9}{2\pi})/2$
Right and Left Thigh	$\frac{DD_{24} + DD_{25}}{4\pi}$	$\frac{DD_{24} + DD_{25}}{4\pi}$	$(DD_1 - DD_5 - DD_{23} + \frac{DD_{24} + DD_{26}}{\pi})/2$
Right and Left Calf	$\frac{DD_{27}}{2\pi}$	$\frac{DD_{27}}{2\pi}$	$(DD_{23} - DD_{29} + \frac{DD_{28}}{2\pi})/2$
Right and Left Foot	$\frac{DD_{29}}{2}$	$\frac{DD_{30}}{2}$	$\frac{DD_{31}}{2}$
Right and Left Upper Arm	$\frac{DD_{19}}{2\pi}$	$\frac{DD_{19}}{2\pi}$	$\frac{DD_{17}}{2}$
Right and Left Forearm	$\frac{DD_{21}}{2\pi}$	$\frac{DD_{21}}{2\pi}$	$\frac{DD_{18}}{2}$

Since none of the 32 body measurements being used give tenth rib height, the landmarks located in the two stereophotometric studies (Baughman, 1981 and McConville et al., 1980) were examined. It was found that the ratio of thorax height (vertical distance between suprasternale and tenth rib midspine) to abdomen height (vertical distance between tenth rib midspine and right iliac crest) averages about 4:1. Using this result the distance between the thorax-abdomen joint and the abdomen-pelvis height was set to be one-fifth of the difference between shoulder height and waist height $[(DD_2 - DD_4)/5]$.

When developing the expressions for torso joint locations, these locations were first laid out in a global setting, with axes origin on the floor (that is vertical distance from the floor). The top of the thorax was determined by shoulder height (DD_2), and the distance from the floor to the bottom of the pelvis was taken as the difference between standing height and seated height ($DD_1 - DD_5$). The center of the abdomen was then located by waist height (DD_4). The abdomen-pelvis joint and the thorax-abdomen joint were located so that the center of the abdomen is mid-way between these two joints (recall that the distance between these two joints is $[(DD_2 - DD_4)/5]$). The center of the thorax was then placed mid-way between the thorax abdomen joint and top of the torso, and the center of the pelvis was placed mid-way between the bottom of the pelvis and the abdomen-pelvis joint. From these global locations the expressions for local reference system coordinates of torso joints were determined.

The Z semiaxis of the pelvis contact ellipsoid is set to the distance from center of the pelvis to the abdomen-pelvis joint. This causes the pelvis contact ellipsoid to cover the pelvis vertically from the abdomen-pelvis joint to the bottom of the pelvis ($DD_1 - DD_5$), since the pelvis center is mid-way between these points. Similarly, the Z semiaxis of the thorax contact ellipsoid is set to the distance from center of the thorax to the thorax-abdomen joint, which results in the contact ellipsoid covering the thorax from the top of the thorax (DD_2) to the thorax-abdomen joint. For the resulting model to

have a proper appearance there must be some overlap between adjacent contact ellipsoids. Since this overlap is primarily for appearance, the extent of overlap utilized is the neck radius ($DD_{29}/2\pi$). This is the amount that the abdomen contact ellipsoid overlaps both the thorax contact ellipsoid and the pelvis contact ellipsoid.

3.2 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF THE HEAD AND NECK

As in the torso, segment centers and joint locations involving the head and neck were first laid out globally. First, the top of the head was placed at standing height (DD_1), and the neck-thorax joint was placed at shoulder height (DD_2). In order to provide overlap the Z semiaxis of the head is set to one half the quantity head height plus neck radius

$$[(DD_8 + \frac{DD_9}{2\pi})/2].$$

The center of the head is then determined by standing height minus the Z semiaxis of the head, and the head-neck joint is located by standing height minus twice the Z semiaxis of the head. The center of the neck is located mid-way between the head-neck joint and the neck-thorax joint. The top of the neck contact ellipsoid is desired to be at standing height minus head height ($DD_1 - DD_8$), so the Z semiaxis of the neck contact ellipsoid is set to the distance between this location and the center of the neck.

3.3 DETERMINING EXPRESSIONS FOR ANKLE LOCATIONS RELATIVE TO THE FEET

As with other limb segments, the Z reference axis of either foot runs the length of the segment (from heel to toe, see Figure 2). For simplicity in developing expressions for joint locations, the foot is viewed in a normal position for a standing model. This rotates the foot reference system 90° from the reference system of other systems, i.e. Z forward, X upward, and Y to the right. The ankle joint is then

a vertical distance of ankle height (DD_{29}) from the bottom of the foot, or one half this distance from the center of the foot. In the 2-horizontal direction the ankle joint is located as being ankle radius ($DD_{29}/2\pi$) in front of the back of the foot, and the center of the foot is located at one-half foot length ($DD_{31}/2$) from the back of the foot in this direction.

3.4 DETERMINING EXPRESSIONS FOR JOINT LOCATIONS AND SEMIAXES OF LIMB SEGMENTS

The remainder of the joint and semiaxis expressions were taken directly from Program GOOD. A concept used in developing expressions for many of these semiaxes and joint locations is that of spherical joints. The usage of this concept is illustrated in Figure 3.

3.5 CONCLUSION

Using the criteria discussed, the expressions in Table 2 for joint locations and the expressions in Table 3 for contact ellipsoid semiaxes have been developed. When used with a set of the 32 body dimensions corresponding to a subject of a specific type and size, these expressions provide values necessary to determine the structure and appearance of the human model utilized by the ATB Model.




Figure 3. Spherical Joint Concept Developed for Program GOOD and Used to Determine Joint Locations Relative to Limb Segments.

Radii of these spheres are as follows:

Shoulder Sphere	$DD_{19}/(2\pi)$
Elbow Sphere	$DD_{20}/(2\pi)$
Wrist Sphere	$DD_{22}/(2\pi)$
Hip Sphere	$DD_{24}/(2\pi)$
Knee Sphere	$DD_{26}/(2\pi)$
Ankle Sphere	$DD_{28}/(2\pi)$

SECTION 4

INERTIAL PROPERTIES OF BODY SEGMENTS

The inertial properties of a body refer to its mass, principal moments of inertia and associated directions, and the location of its center of gravity. The ATB Model requires direct input of the mass and principal moments of inertia of each segment, as well as the directions of the principal moments, relative to the local reference axes. Use of local reference axis systems, which are located with respect to segment centers of gravity, to specify joint locations indirectly locate the segment centers of gravity. Thus, direct input of center of gravity locations to the ATB Model is not necessary.

The distribution of mass within the human body greatly affects the inertial properties. For simplicity it is assumed that the human body is homogeneous, and thus, each individual body segment is homogeneous and has the same density as does all the other body segments.

Program GOOD determines inertial properties of a segment by calculating the inertial properties of that segment's contact ellipsoid (see Appendix E). These inertial properties are then taken as approximations to the inertial properties of the segment. The density used in these computations is determined by first computing the volume of all the contact ellipsoids combined. From this total a density may be determined such that the mass of all the segments combined will equal the desired total mass of the body (DD_0).

Program GEBOD also uses this technique for computation of inertial properties of the head, neck, upper and forearms, and thighs and calves. For the torso segments and the feet GEBOD uses a technique similar to that developed by Leet (1978). This involves modeling a segment by a right elliptical solid that satisfies two criteria:

- 1) each horizontal cross section (parallel to the local reference XY plane) is an ellipse,
- 2) the center of each of these elliptical cross sections lies on the Z local reference axis.

The inertial properties of this model are then calculated and taken as approximations to the inertial properties of the segment.

The right elliptical solid used for the torso segments is illustrated in Figure 4a. It consists of four pieces. The top is a semi-ellipsoid. Below this are two elliptical frustrums. The bottom of the model consists of another semi-ellipsoid. The right and left feet use identical models which are elliptical frustrums. The dimensions of the frustrums and ellipsoids used in these models are determined from the body dimension data as indicated in Figures 4a and 4b.

Numerical integration is used to compute inertial properties of the right elliptical solids. Successive approximations are made to the model by stacks of elliptical cylinders. Within each approximation all cylinders are of the same height. Each successive approximation uses more cylinders of a lesser height than the previous. After each approximation the combined volume of all cylinders within the stack is compared back to the combined volume of the previous stack. When the difference between these two volumes drops below a specified tolerance level, the inertial properties of the combined stack of cylinders (see Appendix E) are taken as the inertial properties of the right elliptical solid. These inertial properties are then used as approximations to the inertial properties of the segment in question.

Program GEBOD determines the density to be used in computation of inertial properties in much the same way as does Program GOOD. The combined volume of all models used to determine inertial properties (both ellipsoids and right elliptical solids) is computed and a density is determined so that the total mass of these models will equal the desired total body mass (DD_0). The ratio of this density to the density of water (which approximates average human body density) is listed with other results of Program GEBOD as a weight correction factor.

The center of gravity of the models used to approximate segment inertial properties are taken by GEBOD as the true locations of segment centers of gravity. In developing expressions for joint




Figure 4. Cross Sections of Right Elliptical Solids Used to Approximate Segment Inertial Properties.

- (a) Solid used with thorax segments.
- (b) Solid used with feet segments.

locations (see Section 3), the origins of local reference systems (i.e., segment centers of gravity) were approximated by contact ellipsoid centers. Once GEBOD has developed the models for inertial properties joint location coordinates must be converted, corresponding in each case to a translation of axes from a contact ellipsoid center to the center of gravity of the model used to compute inertial properties. Since an ellipsoid is completely symmetrical, its center of gravity is located at its center, which agrees with the assumed location of the local reference systems. The right elliptical solids, however, are only symmetric about the Z axis. So, in general, the location of the center of gravity of this model does not correspond with its center in the Z direction. The torso segments and feet segments, which use this type model in computation of their inertial properties, are the only segments in which the center of gravity does not coincide with the center of the contact ellipsoid. Because this moves the location of the local reference system of these segments in the Z direction, the Z coordinates of joints located relative to these segments are adjusted for this change, after computation of inertial properties. This adjustment of joint Z coordinates completes the computations performed by GEBOD in order to determine body description data.


APPENDIX A


USER'S GUIDE


The computer program GEBOD was written in Perkin-Elmer Fortran VII and was developed and tested on the Perkin-Elmer 3240 located at Building 441, Wright-Patterson Air Force Base; Dayton, Ohio. This version of the Fortran VII programming language meets the ANSI '77 standard for Fortran, and thus, GEBOD should be portable to any system supporting an ANSI '77 standard Fortran.

GEBOD utilizes five logical units. Prompts for the user are written to logical unit 5. User input is received through unit 7. Body description data produced by GEBOD is written to both units 3 and 9. Data written to unit 3 is ready for insertion into the ATB Model input deck, whereas the data written to unit 9 (see Appendix B), is a tabular presentation of the data. If the user chooses to supply a specific set of the 32 body dimensions (see Table 1), this data is received through unit 1. The data must be supplied in four 80 character records, each record containing values for 8 of the body measurements. The values for the body measurements are listed in sequential order on these records with each record using an (8F10.3) format.

The remainder of this appendix is a flowchart describing options available to the user of GEBOD.







APPENDIX B
SAMPLE OUTPUT FROM PROGRAM GEBOD

TEST OF 5'10" MALE WEIGHING 150LB.

ADULT MALE

SELECTED BODY DIMENSIONS

WEIGHT	150.0	LBS
STANDING HEIGHT	70.00	IN

COMPUTED BODY DIMENSIONS

0	WEIGHT	68.04	KGRAMS
1	STANDING HEIGHT	177.8	CM
2	SHOULDER HEIGHT	145.1	CM
3	ARMPIT HEIGHT	130.4	CM
4	WAIST HEIGHT	107.2	CM
5	SEATED HEIGHT	93.12	CM
6	HEAD LENGTH	19.74	CM
7	HEAD BREADTH	15.42	CM
8	HEAD TO CHIN HEIGHT	22.79	CM
9	NECK CIRCUMFERENCE	36.63	CM
10	SHOULDER BREADTH	40.01	CM
11	CHEST DEPTH	22.58	CM
12	CHEST BREADTH	30.80	CM
13	WAIST DEPTH	20.03	CM
14	WAIST BREADTH	28.39	CM
15	BUTTOCK DEPTH	21.75	CM
16	HIP BREADTH, STANDING	33.59	CM
17	SHOULDER TO ELBOW LENGTH	36.05	CM
18	FOREARM-HAND LENGTH	49.41	CM
19	BICEPS CIRCUMFERENCE	29.01	CM
20	ELBOW CIRCUMFERENCE	30.19	CM
21	FOREARM CIRCUMFERENCE	26.74	CM
22	WRIST CIRCUMFERENCE	17.03	CM
23	KNEE HEIGHT, SEATED	55.61	CM
24	THIGH CIRCUMFERENCE	53.79	CM
25	UPPER LEG CIRCUMFERENCE	36.74	CM
26	KNEE CIRCUMFERENCE	37.30	CM
27	CALF CIRCUMFERENCE	34.92	CM
28	ANKLE CIRCUMFERENCE	21.41	CM
29	ANKLE HEIGHT, OUTSIDE	13.83	CM
30	FOOT BREADTH	9.601	CM
31	FOOT LENGTH	26.88	CM

WEIGHT CORRECTION FACTOR = 1.110

TEST OF 5'10" MALE WEIGHING 150LB.

CRASH VICTIM PARAMETERS (3-D)

SEGMENT NO. SYM PLOT	MASS (KG.)	SEGMENT MOMENT OF INERTIA (KG-M ²)			SEGMENT CONTACT ELLIPSOID SEMIAxis (CM)			CENTER (CM)		
		X	Y	Z	X	Y	Z	X	Y	Z
1 LT 1	11.389	0.10929	0.06578	0.10943	10.88	16.79	9.37	0.00	0.00	-0.28
2 CT 2	3.856	0.02210	0.01184	0.03018	10.01	14.20	9.62	0.00	0.00	-0.02
3 UT 3	16.787	0.21751	0.17534	0.13616	11.29	15.40	17.04	0.00	0.00	-1.78
4 M 4	1.244	0.00241	0.00241	0.00170	5.83	5.83	7.88	0.00	0.00	0.00
5 H 5	5.062	0.02696	0.03084	0.01601	9.87	7.71	14.31	0.00	0.00	0.00
6 RUL 6	7.004	0.12632	0.12632	0.01465	7.20	7.20	29.03	0.00	0.00	0.00
7 RLL 7	3.243	0.03539	0.03539	0.00404	5.56	5.56	22.59	0.00	0.00	0.00
8 RF 8	0.737	0.00337	0.00326	0.00404	6.91	4.80	13.44	0.00	0.00	3.46
9 LUL 9	7.004	0.12632	0.12632	0.01465	7.20	7.20	29.03	0.00	0.00	0.00
10 LLL A	3.243	0.03539	0.03539	0.00404	5.56	5.56	22.59	0.00	0.00	0.00
11 LF B	0.737	0.00337	0.00326	0.00404	6.91	4.80	13.44	0.00	0.00	3.46
12 RUA C	1.785	0.01246	0.01246	0.00153	4.62	4.62	18.03	0.00	0.00	0.00
13 RLA D	2.080	0.02634	0.02634	0.00152	4.26	4.26	24.71	0.00	0.00	0.00
14 LUA E	1.785	0.01246	0.01246	0.00153	4.62	4.62	18.03	0.00	0.00	0.00
15 LLA F	2.080	0.02634	0.02634	0.00152	4.26	4.26	24.71	0.00	0.00	0.00

JOINT J SYM PLOT JNT PIN	LOCATION(CM)	X	Y	Z	SEG(J+1)	PRIN. AXIS(1)			SEG(JNT)	PRIN. AXIS(DEG)			SEG(J+1)
						X	Y	Z		ROLL	PITCH	YAW	
1 P M 1 0	0.00	0.00	0.00	-9.65	0.00	0.00	0.00	3.76	0.00	0.00	0.00	0.00	0.00
2 M M 2 0	0.00	0.00	0.00	-3.81	0.00	0.00	0.00	15.26	0.00	0.00	0.00	0.00	0.00
3 MP 0 3 0	0.00	0.00	0.00	-18.83	0.00	0.00	0.00	2.05	0.00	0.00	0.00	0.00	0.00
4 MP P 4 0	0.00	0.00	0.00	-2.05	0.00	0.00	0.00	14.31	0.00	0.00	0.00	0.00	0.00
5 RH Q 1 0	0.00	0.00	0.00	0.53	0.00	0.00	0.00	-20.47	0.00	0.00	0.00	0.00	0.00
6 RK R 6 1	0.00	0.00	0.00	23.10	0.00	0.00	0.00	-16.66	0.00	0.00	0.00	0.00	0.00
7 RA S 7 0	0.00	0.00	0.00	19.19	6.91	0.00	0.00	-6.57	0.00	0.00	0.00	0.00	0.00
8 LM T 1 0	0.00	0.00	0.00	0.53	0.00	0.00	0.00	-20.47	0.00	0.00	0.00	0.00	0.00
9 LK U 9 1	0.00	0.00	0.00	23.10	0.00	0.00	0.00	-16.66	0.00	0.00	0.00	0.00	0.00
10 LA U 10 0	0.00	0.00	0.00	19.19	6.91	0.00	0.00	-6.57	0.00	0.00	0.00	0.00	0.00
11 RS W 3 0	0.00	0.00	0.00	-11.81	0.00	0.00	0.00	-13.41	0.00	0.00	0.00	0.00	0.00
12 RE X 12 1	0.00	0.00	0.00	13.22	0.00	0.00	0.00	-19.90	0.00	0.00	0.00	0.00	0.00
13 LS Y 3 0	0.00	0.00	0.00	-15.39	0.00	0.00	0.00	-13.41	0.00	0.00	0.00	0.00	0.00
14 LE Z 14 1	0.00	0.00	0.00	13.22	0.00	0.00	0.00	-19.90	0.00	0.00	0.00	0.00	0.00

APPENDIX C COMPARISON OF REGRESSION TO PERCENTILE BASIS FOR BODY DIMENSIONS

Program GOOD computes values of body dimensions for a particular subject by using two fixed percentiles. The user selects a percentile for stature, and dimensions 23 through 31 (see Table 1) are computed to be the same percentile. The user also selects a percentile for sitting height, and dimensions 2 through 22 and 32 and 33 are computed to be this percentile. The percentile values are computed by use of a mean value and standard deviation for each body dimension, along with the assumption that each of the body dimension measurements are normally distributed.

The problem with this approach is that when component dimensions are all set to a fixed percentile, the resulting whole is of a different percentile. This can be illustrated by considering three populations A, B, and C. Each of these populations consists of n measurements, referred to as a_i, b_i, c_i ($i = 1, n$), and for each i ($i = 1, n$) $a_i + b_i = c_i$. The mean of the A, B, and C populations are \bar{a}, \bar{b} , and \bar{c} , respectively, and s_a, s_b, s_c are the respective standard deviations of the three populations. Assuming a normal distribution for each of the populations, a specific percentile point may be computed as being a certain number of standard deviations away from the mean. Thus if a_m, b_m , and c_m are the m^{th} percentile points of their respective populations, there exists an α such that $a_m = \bar{a} + \alpha s_a$, $b_m = \bar{b} + \alpha s_b$, and $c_m = \bar{c} + \alpha s_c$. Ideally $a_m + b_m = c_m$, however, in general this is not the case, as is shown in the following:

$$\begin{aligned}
 c_m &= \bar{c} + \alpha s_c \\
 &= \frac{1}{n} \sum c_i + \frac{\alpha}{n-1} \left[\sum \left(c_i - \frac{\sum c_i}{n} \right)^2 \right] \\
 &= \frac{1}{n} \sum (a_i + b_i) + \frac{\alpha}{n-1} \left[\sum \left(a_i + b_i - \frac{\sum (a_i + b_i)}{n} \right)^2 \right] \\
 &= \bar{a} + \bar{b} + \frac{\alpha}{n-1} \left[\sum ((a_i - \bar{a}) + (b_i - \bar{b}))^2 \right]
 \end{aligned}$$

$$\begin{aligned}
&= \bar{a} + \bar{b} + \frac{\alpha}{n-1} [\Sigma(a_i - \bar{a})^2 + \Sigma(b_i - \bar{b})^2 + 2\Sigma(a_i - \bar{a})(b_i - \bar{b})] \\
&= a + \alpha S_a + \bar{b} + \alpha S_b + \frac{2\alpha}{n-1} [\Sigma(a_i - \bar{a})(b_i - \bar{b})] \\
&= a_m + b_m + \frac{2\alpha}{n-1} [\Sigma(a_i - \bar{a})(b_i - \bar{b})]
\end{aligned}$$

where the usual definitions of mean and standard deviation ($a = \frac{1}{n} \Sigma a_i$, $s_a = \frac{1}{n-1} \Sigma(a_i - a)^2$, etc.) have been used.

The method used by GEBOD, to determine body dimension values corresponding to a particular subject, is to regress each body dimension against age (for children only), height, and/or weight (see Appendix D). Using the A, B, and C populations to illustrate this method also, least squares linear regressions equations would be developed expressing values from the A and B populations as functions of values from the C populations. That is, the coefficients p_a , q_a , p_b , and q_b would be computed such $a_o = p_a c_o + q_a$ and $b_o = p_b c_o + q_b$, where a_o is the least squares value from the A population corresponding to c_o (a value from the C population), and b_o is the least squares value from the B population corresponding to c_o . Using standard least squares techniques the values of these parameters are computed as follows:

$$\begin{aligned}
p_a &= \frac{\Sigma(a_i - \bar{a})(c_i - \bar{c})}{\Sigma(c_i - \bar{c})^2}, & q_a &= \bar{a} - p_a \bar{c} \\
p_b &= \frac{\Sigma(b_i - \bar{b})(c_i - \bar{c})}{\Sigma(c_i - \bar{c})^2}, & q_b &= \bar{b} - p_b \bar{c}.
\end{aligned}$$

The additivity that does not occur with the percentile method can be shown to exist for this regression technique. The first step in showing this is to establish the result $p_a + p_b = 1$:

$$p_a + p_b = \frac{\Sigma(a_i - \bar{a})(c_i - \bar{c})}{\Sigma(c_i - \bar{c})^2} + \frac{\Sigma(b_i - \bar{b})(c_i - \bar{c})}{\Sigma(c_i - \bar{c})^2}$$

$$\begin{aligned}
&= \frac{\sum [(c_i - \bar{c}) ((a_i - \bar{a}) + (b_i - \bar{b}))]}{\sum (c_i - \bar{c})^2} \\
&= \frac{\sum [(c_i - \bar{c}) (a_i + b_i - (\bar{a} + \bar{b}))]}{\sum (c_i - \bar{c})^2} \\
&= \frac{\sum [(c_i - \bar{c})^2]}{\sum (c_i - \bar{c})^2} \\
&= 1 .
\end{aligned}$$

Using this result it can be shown that values from the A and B populations, a_o , and b_o , respectively, both corresponding to the same value of the C population, c_o , sum to that value of the C population:

$$\begin{aligned}
a_o + b_o &= p_a c_o + q_a + p_b c_o + q_b \\
&= c_o (p_a + p_b) + (q_a + q_b) \\
&= c_o + (\bar{a} - p_a \bar{c} + \bar{b} - p_b \bar{c}) \\
&= c_o + (\bar{a} + \bar{b}) - \bar{c} (p_a + p_b) \\
&= c_o + \bar{c} - \bar{c} \\
&= c_o .
\end{aligned}$$

It is for this reason of additivity, that a regression approach was felt to be more correct than the percentile approach of program GOOD as a method of determining body dimensions corresponding to a particular subject, and was therefore used in program GEBOD.

APPENDIX D
BODY DIMENSION REGRESSION EQUATIONS DEVELOPED FOR GEBOD

This appendix contains a complete listing of the regression equations developed for use by GEBOD. For the adult male and female sets heights and weight are used as predicting variables. The child set uses age along with height and weight. At the top of each set of regression equations is listed the range of values, mean, and standard deviation of the predicting variables within that subject type. For each body dimension a separate regression equation is given against each of the predicting variables. The last regression equation given for each body dimension is a step-wise multiple regression against all of the predicting variables. Since this is a step-wise regression, only those predicting variables that would make a significant contribution to the regression appear in the final form of the regression equation. With each regression equation the square of the correlation coefficient (R^2) and the number of subjects the regression equation is based on (NSUB) are given.

REGRESSION EQUATIONS FOR ADULT FEMALES

PREDICTING VARIABLES		RANGE:		MEAN:		S.D.:	
WEIGHT		85.00	200.0	127.3	16.59		
STANDING HEIGHT		56.93	72.03	63.82	2.364		
REGRESSION EQUATIONS FOR WEIGHT							
WEIGHT	= 1.000	*WEIGHT	+ .4547E-12		R**2 = 1.0000	NSUB = 1905	
WEIGHT	= 3.737	*STANDING	-111.2		R**2 = .2836	NSUB = 1905	
WEIGHT	= 1.000	*WEIGHT	+ .4547E-12		R**2 = 1.0000	NSUB = 1905	
REGRESSION EQUATIONS FOR STANDING HEIGHT							
STANDING HEIGHT	= .7589E-01	*WEIGHT	+54.16		R**2 = .2836	NSUB = 1905	
STANDING HEIGHT	= 1.000	*STANDING	+ .2274E-12		R**2 = 1.0000	NSUB = 1905	
STANDING HEIGHT	= 1.000	*STANDING	+ .2274E-12		R**2 = 1.0000	NSUB = 1905	
REGRESSION EQUATIONS FOR SHOULDER HEIGHT							
SHOULDER HEIGHT	= .7182E-01	*WEIGHT	+42.77		R**2 = .3049	NSUB = 1905	
SHOULDER HEIGHT	= .8751	*STANDING	-3.936		R**2 = .9194	NSUB = 1905	
SHOULDER HEIGHT	= .7555E-02	*WEIGHT	+ .9469	*STANDING -3.096	R**2 = .9218	NSUB = 1905	
REGRESSION EQUATIONS FOR ARMPIT HEIGHT							
ARMPIT HEIGHT	= .5840E-01	*WEIGHT	+39.83		R**2 = .2217	NSUB = 1905	
ARMPIT HEIGHT	= .8309	*STANDING	-5.762		R**2 = .9115	NSUB = 1905	
ARMPIT HEIGHT	= .6495E-02	*WEIGHT	+ .8551	*STANDING -6.484	R**2 = .9135	NSUB = 1905	
REGRESSION EQUATIONS FOR WAIST HEIGHT							
WAIST HEIGHT	= .5302E-01	*WEIGHT	+32.73		R**2 = .2465	NSUB = 1905	
WAIST HEIGHT	= .6845	*STANDING	-4.206		R**2 = .8346	NSUB = 1905	
WAIST HEIGHT	= .6845	*STANDING	-4.206		R**2 = .8346	NSUB = 1905	
REGRESSION EQUATIONS FOR SEATED HEIGHT							
SEATED HEIGHT	= .3620E-01	*WEIGHT	+29.09		R**2 = .2317	NSUB = 1905	
SEATED HEIGHT	= .4225	*STANDING	+6.734		R**2 = .6409	NSUB = 1905	
SEATED HEIGHT	= .5773E-02	*WEIGHT	+ .4010	*STANDING +7.376	R**2 = .6451	NSUB = 1905	
REGRESSION EQUATIONS FOR HEAD LENGTH							
HEAD LENGTH	= .4897E-02	*WEIGHT	+6.625		R**2 = .0923	NSUB = 1905	
HEAD LENGTH	= .3600E-01	*STANDING	+4.950		R**2 = .1014	NSUB = 1905	
HEAD LENGTH	= .3921E-02	*WEIGHT	+ .2471E-01	*STANDING +5.286	R**2 = .1265	NSUB = 1905	
REGRESSION EQUATIONS FOR HEAD BREADTH							
HEAD BREADTH	= .4089E-02	*WEIGHT	+5.194		R**2 = .0839	NSUB = 1905	
HEAD BREADTH	= .1347E-01	*STANDING	+4.855		R**2 = .0185	NSUB = 1905	
HEAD BREADTH	= .4089E-02	*WEIGHT	+5.194		R**2 = .0839	NSUB = 1905	

REGRESSION EQUATIONS FOR HEAD TO CHIN HEIGHT
HEAD TO CHIN HEIGHT = .7362E-02*WEIGHT +7.688
HEAD TO CHIN HEIGHT = .6816E-01*STANDING +4.275
HEAD TO CHIN HEIGHT = .3057E-02*WEIGHT +.5674E-01*STANDING +4.615
R**2 = .0741 NSUB = 1905
R**2 = .1290 NSUB = 1905
R**2 = .1382 NSUB = 1905

REGRESSION EQUATIONS FOR NECK CIRCUMFERENCE
NECK CIRCUMFERENCE = .2316E-01*WEIGHT +10.34
NECK CIRCUMFERENCE = .8900E-01*STANDING +7.607
NECK CIRCUMFERENCE = .2316E-01*WEIGHT +10.34
R**2 = .3387 NSUB = 1905
R**2 = .1016 NSUB = 1905
R**2 = .3387 NSUB = 1905

REGRESSION EQUATIONS FOR SHOULDER BREADTH
SHOULDER BREADTH = .1927E-01*WEIGHT +11.66
SHOULDER BREADTH = .1246 *STANDING +6.160
SHOULDER BREADTH = .1369E-01*WEIGHT +.7344E-01*STANDING +7.682
R**2 = .2451 NSUB = 1905
R**2 = .2082 NSUB = 1905
R**2 = .2969 NSUB = 1905

REGRESSION EQUATIONS FOR CHEST DEPTH
CHEST DEPTH = .3412E-01*WEIGHT +4.965
CHEST DEPTH = .7300E-01*STANDING +4.650
CHEST DEPTH = .3989E-01*WEIGHT -.7607E-01*STANDING +9.086
R**2 = .5535 NSUB = 1905
R**2 = .0515 NSUB = 1905
R**2 = .5536 NSUB = 1905

REGRESSION EQUATIONS FOR CHEST BREADTH
CHEST BREADTH = .3185E-01*WEIGHT +6.968
CHEST BREADTH = .8875E-01*STANDING +5.357
CHEST BREADTH = .3505E-01*WEIGHT -.4222E-01*STANDING +9.255
R**2 = .4912 NSUB = 1905
R**2 = .0775 NSUB = 1905
R**2 = .5037 NSUB = 1905

REGRESSION EQUATIONS FOR WAIST DEPTH
WAIST DEPTH = .2922E-01*WEIGHT +2.979
WAIST DEPTH = .5358E-01*STANDING +3.279
WAIST DEPTH = .3511E-01*WEIGHT -.7761E-01*STANDING +7.183
R**2 = .5422 NSUB = 1905
R**2 = .0370 NSUB = 1905
R**2 = .5579 NSUB = 1905

REGRESSION EQUATIONS FOR WAIST BREADTH
WAIST BREADTH = .3527E-01*WEIGHT +5.010
WAIST BREADTH = .1060 *STANDING +2.734
WAIST BREADTH = .3800E-01*WEIGHT -.3598E-01*STANDING +6.959
R**2 = .5892 NSUB = 1905
R**2 = .1081 NSUB = 1905
R**2 = .5981 NSUB = 1905

REGRESSION EQUATIONS FOR BUTTOCK DEPTH
BUTTOCK DEPTH = .3419E-01*WEIGHT +3.976
BUTTOCK DEPTH = .7050E-01*STANDING +3.803
BUTTOCK DEPTH = .4021E-01*WEIGHT -.7937E-01*STANDING +6.275
R**2 = .6477 NSUB = 1905
R**2 = .0566 NSUB = 1905
R**2 = .6985 NSUB = 1905

REGRESSION EQUATIONS FOR HIP BREADTH, STANDING
HIP BREADTH, STANDING = .4052E-01*WEIGHT +8.610
HIP BREADTH, STANDING = .1285 *STANDING +5.563
HIP BREADTH, STANDING = .4294E-01*WEIGHT -.3192E-01*STANDING +10.34
R**2 = .5935 NSUB = 1905
R**2 = .1213 NSUB = 1905
R**2 = .5988 NSUB = 1905

REGRESSION EQUATIONS FOR SHOULDER TO ELBOW LENGTH		
SHOULDER TO ELBOW = .1702E-01*HEIGHT +10.04		
SHOULDER TO ELBOW = .1962 *STANDING - .3163		
SHOULDER TO ELBOW = .2976E-02*HEIGHT +.1051		
	*STANDING +.1459E-01	R _{ee2} = .1946 P _{ee2} = .5252 R _{ee2} = .5295 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR FOREARM-HAND LENGTH		
FOREARM-HAND LENGT = .2092E-01*HEIGHT +13.70		
FOREARM-HAND LENGT = .2478 *STANDING +.6324		
FOREARM-HAND LENGT = .2960E-02*HEIGHT +.2367		
	*STANDING +.9615	R _{ee2} = .1941 R _{ee2} = .5526 R _{ee2} = .5554 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR BICEPS CIRCUMFERENCE		
BICEPS CIRCUMFEREN = .4369E-01*HEIGHT +4.522		
BICEPS CIRCUMFEREN = .5386E-01*STANDING +6.646		
BICEPS CIRCUMFEREN = .5528E-01*HEIGHT -.1527		
	*STANDING +12.79	R _{ee2} = .6442 R _{ee2} = .0199 R _{ee2} = .7587 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR ELBOW CIRCUMFERENCE		
ELBOW CIRCUMFERENC = .2421E-01*HEIGHT +7.539		
ELBOW CIRCUMFERENC = .1221 *STANDING +2.826		
ELBOW CIRCUMFERENC = .2086E-01*HEIGHT +.4420E-01*STANDING +5.145		
		R _{ee2} = .3274 R _{ee2} = .1692 R _{ee2} = .3433 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR FOREARM CIRCUMFERENCE		
FOREARM CIRCUMFERE = .2643E-01*HEIGHT +5.879		
FOREARM CIRCUMFERE = .7088E-01*STANDING +4.719		
FOREARM CIRCUMFERE = .2938E-01*HEIGHT -.3890E-01*STANDING +7.986		
		R _{ee2} = .6524 R _{ee2} = .0953 R _{ee2} = .6730 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR WRIST CIRCUMFERENCE		
WRIST CIRCUMFERENC = .1090E-01*HEIGHT +4.503		
WRIST CIRCUMFERENC = .5371E-01*STANDING +2.463		
WRIST CIRCUMFERENC = .9530E-02*HEIGHT +.1810E-01*STANDING +3.523		
		R _{ee2} = .4168 R _{ee2} = .2054 R _{ee2} = .4335 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR KNEE HEIGHT, SEATED		
KNEE HEIGHT, SEATED = .3002E-01*HEIGHT +14.90		
KNEE HEIGHT, SEATED = .3345 *STANDING -2.547		
KNEE HEIGHT, SEATED = .6469E-02*HEIGHT +.3104		
	*STANDING -1.828	R _{ee2} = .2549 R _{ee2} = .6428 R _{ee2} = .6512 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR THIGH CIRCUMFERENCE		
THIGH CIRCUMFERENC = .8417E-01*HEIGHT +11.13		
THIGH CIRCUMFERENC = .1869 *STANDING +9.912		
THIGH CIRCUMFERENC = .9769E-01*HEIGHT -.1701		
	*STANDING +20.77	R _{ee2} = .7063 R _{ee2} = .0707 R _{ee2} = .7523 NSUB = 1905 NSUB = 1905 NSUB = 1905
REGRESSION EQUATIONS FOR UPPER LEG CIRCUMFERENCE		
UPPER LEG CIRCUMFERE = .6412E-01*HEIGHT +9.905		
UPPER LEG CIRCUMFERE = .1664 *STANDING +7.448		
UPPER LEG CIRCUMFERE = .7187E-01*HEIGHT -.1022		
	*STANDING +15.44	R _{ee2} = .7710 R _{ee2} = .1054 R _{ee2} = .7995 NSUB = 1905 NSUB = 1905 NSUB = 1905

REGRESSION EQUATIONS FOR KNEE CIRCUMFERENCE
 KNEE CIRCUMFERENCE = .4406E-01*WEIGHT +8.684
 KNEE CIRCUMFERENCE = .1458 *STANDING +4.985
 KNEE CIRCUMFERENCE = .4603E-01*WEIGHT -.2626E-01*STANDING +10.11
 R² = .6714 NSUB = 1905
 R² = .1494 NSUB = 1905
 R² = .6749 NSUB = 1905

REGRESSION EQUATIONS FOR CALF CIRCUMFERENCE
 CALF CIRCUMFERENCE = .4012E-01*WEIGHT +8.335
 CALF CIRCUMFERENCE = .1106 *STANDING +6.386
 CALF CIRCUMFERENCE = .4429E-01*WEIGHT -.3493E-01*STANDING +11.31
 R² = .5661 NSUB = 1905
 R² = .0873 NSUB = 1905
 R² = .5816 NSUB = 1905

REGRESSION EQUATIONS FOR ANKLE CIRCUMFERENCE
 ANKLE CIRCUMFERENCE = .1809E-01*WEIGHT +5.999
 ANKLE CIRCUMFERENCE = .7603E-01*STANDING +3.449
 ANKLE CIRCUMFERENCE = .1720E-01*WEIGHT +.1177E-01*STANDING +5.361
 R² = .3496 NSUB = 1905
 R² = .1254 NSUB = 1905
 R² = .3517 NSUB = 1905

REGRESSION EQUATIONS FOR ANKLE HEIGHT, OUTSIDE
 ANKLE HEIGHT, OUTSIDE = .3434E-02*WEIGHT +2.230
 ANKLE HEIGHT, OUTSIDE = .4163E-01*STANDING +.9788E-02
 ANKLE HEIGHT, OUTSIDE = .4163E-01*STANDING +.9788E-02
 R² = .0607 NSUB = 1905
 R² = .1813 NSUB = 1905
 R² = .1813 NSUB = 1905

REGRESSION EQUATIONS FOR FOOT BREADTH
 FOOT BREADTH = .4638E-02*WEIGHT +2.901
 FOOT BREADTH = .2947E-01*STANDING +1.611
 FOOT BREADTH = .3353E-02*WEIGHT +.1654E-01*STANDING +1.984
 R² = .1541 NSUB = 1905
 R² = .1263 NSUB = 1905
 R² = .1840 NSUB = 1905

REGRESSION EQUATIONS FOR FOOT LENGTH
 FOOT LENGTH = .1365E-01*WEIGHT +7.738
 FOOT LENGTH = .1299 *STANDING +1.186
 FOOT LENGTH = .5296E-02*WEIGHT +.1101 *STANDING +1.775
 R² = .2601 NSUB = 1905
 R² = .4783 NSUB = 1905
 R² = .5063 NSUB = 1905

REGRESSION EQUATIONS FOR ADULT MALES

PREDICTING VARIABLES		RANGE:	118.0	264.0	MEAN:	173.6	S.D.:	21.44
WEIGHT		RANGE:	62.17	77.64	MEAN:	69.82	S.D.:	2.437
STANDING HEIGHT								
REGRESSION EQUATIONS FOR WEIGHT								
WEIGHT	=	1.000	*WEIGHT	+.9095E-12				
WEIGHT	=	4.530	*STANDING	-142.7				
WEIGHT	=	1.000	*WEIGHT	+.9095E-12				
REGRESSION EQUATIONS FOR STANDING HEIGHT								
STANDING HEIGHT	=	.5850E-01*WEIGHT	+59.66					
STANDING HEIGHT	=	1.000	*STANDING	+.4547E-12				
STANDING HEIGHT	=	1.000	*STANDING	+.4547E-12				
REGRESSION EQUATIONS FOR SHOULDER HEIGHT								
SHOULDER HEIGHT	=	.5844E-01*WEIGHT	+47.02					
SHOULDER HEIGHT	=	.8911	*STANDING	-5.049				
SHOULDER HEIGHT	=	.8583E-02*WEIGHT	+.8522					
*STANDING -3.824								
REGRESSION EQUATIONS FOR ARMPIT HEIGHT								
ARMPIT HEIGHT	=	.4637E-01*WEIGHT	+43.06					
ARMPIT HEIGHT	=	.8398	*STANDING	-7.529				
ARMPIT HEIGHT	=	-.3761E-02*WEIGHT	+.8569					
*STANDING -8.066								
REGRESSION EQUATIONS FOR WAIST HEIGHT								
WAIST HEIGHT	=	.3642E-01*WEIGHT	+35.59					
WAIST HEIGHT	=	.7043	*STANDING	-7.256				
WAIST HEIGHT	=	-.6506E-02*WEIGHT	+.7338					
*STANDING -8.185								
REGRESSION EQUATIONS FOR SEATED HEIGHT								
SEATED HEIGHT	=	.2664E-01*WEIGHT	+32.06					
SEATED HEIGHT	=	.4043	*STANDING	+8.460				
SEATED HEIGHT	=	.4060E-02*WEIGHT	+.3859					
*STANDING +9.039								
REGRESSION EQUATIONS FOR HEAD LENGTH								
HEAD LENGTH	=	.3209E-02*WEIGHT	+7.266					
HEAD LENGTH	=	.2680E-01*STANDING	+5.952					
HEAD LENGTH	=	.2233E-02*WEIGHT	+.1668E-01*STANDING					
+6.271								
REGRESSION EQUATIONS FOR HEAD BREADTH								
HEAD BREADTH	=	.3060E-02*WEIGHT	+5.611					
HEAD BREADTH	=	.1174E-01*STANDING	+5.322					
HEAD BREADTH	=	.3060E-02*WEIGHT	+5.611					

REGRESSION EQUATIONS FOR HEAD TO CHIN HEIGHT		
HEAD TO CHIN HEIGHT = .3143E-01*WEIGHT	+8.420	NSUB = 2420
HEAD TO CHIN HEIGHT = .4659E-01*STANDING	+5.712	NSUB = 2420
HEAD TO CHIN HEIGHT = .4659E-01*STANDING	+5.712	NSUB = 2420
R _{ee2} =	.0281	
R _{ee2} =	.0796	
R _{ee2} =	.0796	
REGRESSION EQUATIONS FOR NECK CIRCUMFERENCE		
NECK CIRCUMFERENCE = .2444E-01*WEIGHT	+10.95	NSUB = 2420
NECK CIRCUMFERENCE = .5327E-01*STANDING	+10.54	NSUB = 2420
NECK CIRCUMFERENCE = .2808E-01*WEIGHT	-.6185E-01*STANDING	+14.54
R _{ee2} =	.4865	
R _{ee2} =	.0448	
R _{ee2} =	.5160	
REGRESSION EQUATIONS FOR SHOULDER BREADTH		
SHOULDER BREADTH = .1612E-01*WEIGHT	+13.24	NSUB = 2420
SHOULDER BREADTH = .1181 *STANDING	+7.790	NSUB = 2420
SHOULDER BREADTH = .1253E-01*WEIGHT	+.6133E-01*STANDING	+9.578
R _{ee2} =	.2043	
R _{ee2} =	.1416	
R _{ee2} =	.2323	
REGRESSION EQUATIONS FOR CHEST DEPTH		
CHEST DEPTH = .2690E-01*WEIGHT	+4.984	NSUB = 2420
CHEST DEPTH = .5114E-01*STANDING	+5.386	NSUB = 2420
CHEST DEPTH = .3174E-01*WEIGHT	-.8265E-01*STANDING	+9.915
R _{ee2} =	.5767	
R _{ee2} =	.0385	
R _{ee2} =	.6284	
REGRESSION EQUATIONS FOR CHEST BREADTH		
CHEST BREADTH = .2911E-01*WEIGHT	+7.854	NSUB = 2420
CHEST BREADTH = .8877E-01*STANDING	+6.709	NSUB = 2420
CHEST BREADTH = .3254E-01*WEIGHT	-.5866E-01*STANDING	+11.35
R _{ee2} =	.5608	
R _{ee2} =	.0673	
R _{ee2} =	.5824	
REGRESSION EQUATIONS FOR WAIST DEPTH		
WAIST DEPTH = .3026E-01*WEIGHT	+3.528	NSUB = 2420
WAIST DEPTH = .5167E-01*STANDING	+5.174	NSUB = 2420
WAIST DEPTH = .3706E-01*WEIGHT	-.1162	*STANDING +10.46
R _{ee2} =	.5712	
R _{ee2} =	.0215	
R _{ee2} =	.6512	
REGRESSION EQUATIONS FOR WAIST BREADTH		
WAIST BREADTH = .3741E-01*WEIGHT	+5.694	NSUB = 2420
WAIST BREADTH = .1105 *STANDING	+4.473	NSUB = 2420
WAIST BREADTH = .4211E-01*WEIGHT	-.8025E-01*STANDING	+10.48
R _{ee2} =	.7269	
R _{ee2} =	.0819	
R _{ee2} =	.7586	
REGRESSION EQUATIONS FOR BUTTOCK DEPTH		
BUTTOCK DEPTH = .3077E-01*WEIGHT	+4.095	NSUB = 2420
BUTTOCK DEPTH = .6978E-01*STANDING	+4.566	NSUB = 2420
BUTTOCK DEPTH = .3632E-01*WEIGHT	-.9475E-01*STANDING	+9.749
R _{ee2} =	.6664	
R _{ee2} =	.0442	
R _{ee2} =	.7263	
REGRESSION EQUATIONS FOR HIP BREADTH, STANDING		
HIP BREADTH, STANDING = .2803E-01*WEIGHT	+9.019	NSUB = 2420
HIP BREADTH, STANDING = .1258 *STANDING	+5.100	NSUB = 2420
HIP BREADTH, STANDING = .2803E-01*WEIGHT	+9.019	NSUB = 2420
R _{ee2} =	.6556	
R _{ee2} =	.1706	
R _{ee2} =	.6556	

REGRESSION EQUATIONS FOR SHOULDER TO ELBOW LENGTH

SHOULDER TO ELBOW = .1256E-01*WEIGHT +11.97
 SHOULDER TO ELBOW = .2087 *STANDING -.4158
 SHOULDER TO ELBOW = .2087 *STANDING -.4158
 R**2 = .1595 NSUB = 2420
 R**2 = .5683 NSUB = 2420
 R**2 = .5683 NSUB = 2420

REGRESSION EQUATIONS FOR FOREARM-HAND LENGTH

FOREARM-HAND LENGT = .1671E-01*WEIGHT +16.54
 FOREARM-HAND LENGT = .2646 *STANDING +.9735
 FOREARM-HAND LENGT = .1677E-02*WEIGHT +.2570
 *STANDING +1.213
 R**2 = .1621 NSUB = 2420
 R**2 = .3245 NSUB = 2420
 R**2 = .5258 NSUB = 2420

REGRESSION EQUATIONS FOR BICEPS CIRCUMFERENCE

BICEPS CIRCUMFEREN = .3340E-01*WEIGHT +6.608
 BICEPS CIRCUMFEREN = .5996E-01*STANDING +8.219
 BICEPS CIRCUMFEREN = .4067E-01*WEIGHT -.1243
 *STANDING +14.02
 R**2 = .6711 NSUB = 2420
 R**2 = .0279 NSUB = 2420
 R**2 = .7593 NSUB = 2420

REGRESSION EQUATIONS FOR ELBOW CIRCUMFERENCE

ELBOW CIRCUMFERENC = .1919E-01*WEIGHT +8.967
 ELBOW CIRCUMFERENC = .1061 *STANDING +4.894
 ELBOW CIRCUMFERENC = .1767E-01*WEIGHT +.2601E-01*STANDING +7.416
 R**2 = .3583 NSUB = 2420
 R**2 = .1413 NSUB = 2420
 R**2 = .3645 NSUB = 2420

REGRESSION EQUATIONS FOR FOREARM CIRCUMFERENCE

FOREARM CIRCUMFERE = .2116E-01*WEIGHT +7.411
 FOREARM CIRCUMFERE = .6768E-01*STANDING +6.359
 FOREARM CIRCUMFERE = .2341E-01*WEIGHT -.3835E-01*STANDING +9.700
 R**2 = .6225 NSUB = 2420
 R**2 = .0822 NSUB = 2420
 R**2 = .6419 NSUB = 2420

REGRESSION EQUATIONS FOR WRIST CIRCUMFERENCE

WRIST CIRCUMFERENC = .9921E-02*WEIGHT +5.202
 WRIST CIRCUMFERENC = .5166E-01*STANDING +3.317
 WRIST CIRCUMFERENC = .9386E-02*WEIGHT +.9137E-02*STANDING +4.637
 R**2 = .3446 NSUB = 2420
 R**2 = .1207 NSUB = 2420
 R**2 = .3474 NSUB = 2420

REGRESSION EQUATIONS FOR KNEE HEIGHT, SEATED

KNEE HEIGHT, SEATED = .2467E-01*WEIGHT +17.67
 KNEE HEIGHT, SEATED = .3558 *STANDING -2.889
 KNEE HEIGHT, SEATED = .5244E-02*WEIGHT +.3321
 *STANDING -2.141
 R**2 = .2900 NSUB = 2420
 R**2 = .7789 NSUB = 2420
 R**2 = .7885 NSUB = 2420

REGRESSION EQUATIONS FOR THIGH CIRCUMFERENCE

THIGH CIRCUMFERENC = .6998E-01*WEIGHT +11.01
 THIGH CIRCUMFERENC = .1614 *STANDING +11.89
 THIGH CIRCUMFERENC = .0237E-01*WEIGHT -.2117
 *STANDING +23.64
 R**2 = .7392 NSUB = 2420
 R**2 = .0508 NSUB = 2420
 R**2 = .8034 NSUB = 2420

REGRESSION EQUATIONS FOR UPPER LEG CIRCUMFERENCE

UPPER LEG CIRCUMFE = .3229E-01*WEIGHT +9.621
 UPPER LEG CIRCUMFE = .1412 *STANDING +5.370
 UPPER LEG CIRCUMFE = .3229E-01*WEIGHT +9.621
 R**2 = .7188 NSUB = 2420
 R**2 = .1774 NSUB = 2420
 R**2 = .7188 NSUB = 2420

REGRESSION EQUATIONS FOR KNEE CIRCUMFERENCE
 KNEE CIRCUMFERENCE = .3334E-01*HEIGHT +9.686
 KNEE CIRCUMFERENCE = .1512 *STANDING +4.910
 KNEE CIRCUMFERENCE = .3334E-01*HEIGHT +9.686

R**2 = .7310 NSUB = 2420
 R**2 = .1941 NSUB = 2420
 R**2 = .7310 NSUB = 2420

REGRESSION EQUATIONS FOR CALF CIRCUMFERENCE
 CALF CIRCUMFERENCE = .3250E-01*HEIGHT +9.002
 CALF CIRCUMFERENCE = .0842E-01*STANDING +0.469
 CALF CIRCUMFERENCE = .3710E-01*HEIGHT -.0000E-01*STANDING +13.77

R**2 = .6081 NSUB = 2420
 R**2 = .0581 NSUB = 2420
 R**2 = .6430 NSUB = 2420

REGRESSION EQUATIONS FOR ANKLE CIRCUMFERENCE
 ANKLE CIRCUMFERENCE = .1610E-01*HEIGHT +6.020
 ANKLE CIRCUMFERENCE = .6590E-01*STANDING +4.216
 ANKLE CIRCUMFERENCE = .1665E-01*HEIGHT -.9456E-02*STANDING +6.593

R**2 = .4917 NSUB = 2420
 R**2 = .1045 NSUB = 2420
 R**2 = .4832 NSUB = 2420

REGRESSION EQUATIONS FOR ANKLE HEIGHT, OUTSIDE
 ANKLE HEIGHT, OUTSIDE = .4310E-02*HEIGHT +4.652
 ANKLE HEIGHT, OUTSIDE = .0736E-01*STANDING -.6990
 ANKLE HEIGHT, OUTSIDE = -.1090E-02*HEIGHT +.9230E-01*STANDING -.8545

R**2 = .0419 NSUB = 2420
 R**2 = .2223 NSUB = 2420
 R**2 = .2242 NSUB = 2420

REGRESSION EQUATIONS FOR FOOT BREADTH
 FOOT BREADTH = .4136E-02*HEIGHT +3.127
 FOOT BREADTH = .3418E-01*STANDING +1.459
 FOOT BREADTH = .2907E-02*HEIGHT +.2101E-01*STANDING +1.873

R**2 = .2060 NSUB = 2420
 R**2 = .1824 NSUB = 2420
 R**2 = .2575 NSUB = 2420

REGRESSION EQUATIONS FOR FOOT LENGTH
 FOOT LENGTH = .1020E-01*HEIGHT +0.850
 FOOT LENGTH = .1309 *STANDING +1.502
 FOOT LENGTH = .3570E-02*HEIGHT +.1140 *STANDING +2.012

R**2 = .2214 NSUB = 2420
 R**2 = .4634 NSUB = 2420
 R**2 = .4830 NSUB = 2420

REGRESSION EQUATIONS FOR CHILDREN

PREDICTING VARIABLES		RANGE:	24.00	240.0	MEAN:	124.7	S.D.:	53.02
AGE		RANGE:	22.27	247.6	MEAN:	81.86	S.D.:	39.18
WEIGHT		RANGE:	32.01	76.54	MEAN:	54.52	S.D.:	9.741
STANDING HEIGHT								
REGRESSION EQUATIONS FOR AGE								
AGE	=	1.000	*AGE	+.4547E-12	R**2 =	1.0000	NSUB =	3889
AGE	=	1.213	*WEIGHT	+25.43	R**2 =	.8036	NSUB =	3889
AGE	=	5.202	*STANDING	-158.9	R**2 =	.9136	NSUB =	3889
AGE	=	1.000	*AGE	+.4547E-12	R**2 =	1.0000	NSUB =	3889
REGRESSION EQUATIONS FOR WEIGHT								
WEIGHT	=	.6425	*AGE	-.7660	R**2 =	.8036	NSUB =	3889
WEIGHT	=	1.000	*WEIGHT	+.4547E-12	R**2 =	1.0000	NSUB =	3889
WEIGHT	=	3.743	*STANDING	-122.2	R**2 =	.8629	NSUB =	3889
WEIGHT	=	1.000	*WEIGHT	+.4547E-12	R**2 =	1.0000	NSUB =	3889
REGRESSION EQUATIONS FOR STANDING HEIGHT								
STANDING HEIGHT	=	.1756	*AGE	+32.62	R**2 =	.9136	NSUB =	3889
STANDING HEIGHT	=	.2314	*WEIGHT	+35.58	R**2 =	.8629	NSUB =	3889
STANDING HEIGHT	=	1.000	*STANDING	+.2274E-12	R**2 =	1.0000	NSUB =	3889
STANDING HEIGHT	=	1.000	*STANDING	+.2274E-12	R**2 =	1.0000	NSUB =	3889
REGRESSION EQUATIONS FOR SHOULDER HEIGHT								
SHOULDER HEIGHT	=	.1518	*AGE	+24.79	R**2 =	.9078	NSUB =	1237
SHOULDER HEIGHT	=	.1994	*WEIGHT	+27.37	R**2 =	.8539	NSUB =	1237
SHOULDER HEIGHT	=	.8721	*STANDING	-3.898	R**2 =	.9962	NSUB =	1237
SHOULDER HEIGHT	=	.8721	*STANDING	-3.898	R**2 =	.9962	NSUB =	1237
REGRESSION EQUATIONS FOR ANKLE HEIGHT								
ANKLE HEIGHT	=	.1467	*AGE	+22.53	R**2 =	.9085	NSUB =	1310
ANKLE HEIGHT	=	.1916	*WEIGHT	+25.19	R**2 =	.8475	NSUB =	1310
ANKLE HEIGHT	=	.8315	*STANDING	-4.469	R**2 =	.9921	NSUB =	1310
ANKLE HEIGHT	=	.1217E-01*WEIGHT	+.8770	*STANDING -5.954	R**2 =	.9926	NSUB =	1310
REGRESSION EQUATIONS FOR WAIST HEIGHT								
WAIST HEIGHT	=	.1186	*AGE	+17.74	R**2 =	.8929	NSUB =	1239
WAIST HEIGHT	=	.1530	*WEIGHT	+19.97	R**2 =	.8146	NSUB =	1239
WAIST HEIGHT	=	.6822	*STANDING	-4.726	R**2 =	.9826	NSUB =	1239
WAIST HEIGHT	=	.1855E-01*WEIGHT	+.7519	*STANDING -7.012	R**2 =	.9843	NSUB =	1239
REGRESSION EQUATIONS FOR SEATED HEIGHT								
SEATED HEIGHT	=	.7804E-01*AGE	+19.17		R**2 =	.8944	NSUB =	3848
SEATED HEIGHT	=	.1047	*WEIGHT	+20.34	R**2 =	.8785	NSUB =	3848
SEATED HEIGHT	=	.4412	*STANDING	+4.849	R**2 =	.9641	NSUB =	3848
SEATED HEIGHT	=	.5848E-02*AGE	+.1910E-01*WEIGHT	+.3393	R**2 =	.9686	NSUB =	3848
REGRESSION EQUATIONS FOR HEAD LENGTH								
HEAD LENGTH	=	.3642E-02*AGE	+6.881	*STANDING +8.114	R**2 =	.3224	NSUB =	1297
HEAD LENGTH	=	.5571E-02*WEIGHT	+6.881		R**2 =	.4124	NSUB =	1297
HEAD LENGTH	=	.2249E-01*STANDING	+6.110		R**2 =	.4191	NSUB =	1297
HEAD LENGTH	=	.3975E-02*AGE	+.2793E-02*WEIGHT	+.3264E-01*STANDING +5.825	R**2 =	.4631	NSUB =	1297

REGRESSION EQUATIONS FOR HEAD BREADTH			
HEAD BREADTH	= .3642E-02*AGE	+5.220	
HEAD BREADTH	= .5337E-02*HEIGHT	+5.237	
HEAD BREADTH	= .2096E-01*STANDING	+4.532	
HEAD BREADTH	= -.6471E-03*AGE	+ .3641E-02*HEIGHT	+ .1071E-01*STANDING +4.873
REGRESSION EQUATIONS FOR HEAD TO CHIN HEIGHT			
HEAD TO CHIN HEIGHT	= .8988E-02*AGE	+6.582	
HEAD TO CHIN HEIGHT	= .1266E-01*HEIGHT	+6.666	
HEAD TO CHIN HEIGHT	= .5203E-01*STANDING	+4.867	
HEAD TO CHIN HEIGHT	= -.2157E-02*AGE	+ .4350E-02*HEIGHT	+ .4621E-01*STANDING +5.080
REGRESSION EQUATIONS FOR NECK CIRCUMFERENCE			
NECK CIRCUMFERENCE	= .2281E-01*AGE	+8.421	
NECK CIRCUMFERENCE	= .3449E-01*HEIGHT	+8.448	
NECK CIRCUMFERENCE	= .1301 *STANDING	+4.177	
NECK CIRCUMFERENCE	= -.2812E-02*AGE	+ .3292E-01*HEIGHT	+ .2141E-01*STANDING +7.760
REGRESSION EQUATIONS FOR SHOULDER BREADTH			
SHOULDER BREADTH	= .3595E-01*AGE	+7.930	
SHOULDER BREADTH	= .4866E-01*HEIGHT	+8.020	
SHOULDER BREADTH	= .2040 *STANDING	+ .8749	
SHOULDER BREADTH	= .4037E-02*AGE	+ .1489E-01*HEIGHT	+ .1271 *STANDING +3.354
REGRESSION EQUATIONS FOR CHEST DEPTH			
CHEST DEPTH	= .2870E-01*AGE	+5.225	
CHEST DEPTH	= .4249E-01*HEIGHT	+5.333	
CHEST DEPTH	= .1620 *STANDING	+ .2418E-01	
CHEST DEPTH	= .3764E-01*HEIGHT	+ .2091E-01*STANDING	+4.589
REGRESSION EQUATIONS FOR CHEST BREADTH			
CHEST BREADTH	= .2699E-01*AGE	+5.195	
CHEST BREADTH	= .3856E-01*HEIGHT	+5.411	
CHEST BREADTH	= .1504 *STANDING	+ .3666	
CHEST BREADTH	= .4513E-02*AGE	+ .2798E-01*HEIGHT	+ .2213E-01*STANDING +4.506
REGRESSION EQUATIONS FOR WAIST DEPTH			
WAIST DEPTH	= .1284E-01*AGE	+5.024	
WAIST DEPTH	= .2279E-01*HEIGHT	+4.763	
WAIST DEPTH	= .7598E-01*STANDING	+2.485	
WAIST DEPTH	= -.8176E-02*AGE	+ .3995E-01*HEIGHT	+ .3147E-01*STANDING +6.097
REGRESSION EQUATIONS FOR WAIST BREADTH			
WAIST BREADTH	= .2718E-01*AGE	+5.367	
WAIST BREADTH	= .3977E-01*HEIGHT	+5.508	
WAIST BREADTH	= .1522 *STANDING	+ .4650	
WAIST BREADTH	= .3925E-02*AGE	+ .3503E-01*HEIGHT	+5.406
REGRESSION EQUATIONS FOR BUTTOCK DEPTH			
BUTTOCK DEPTH	= .2730E-01*AGE	+4.812	
BUTTOCK DEPTH	= .4032E-01*HEIGHT	+4.910	
BUTTOCK DEPTH	= .1528 *STANDING	+ .1220	
BUTTOCK DEPTH	= .4893E-02*AGE	+ .3874E-01*HEIGHT	+ .1900E-01*STANDING +5.466

Ree2 = .4591
 Ree2 = .5367
 Ree2 = .5129
 Ree2 = .5469

NSUB = 3782
 NSUB = 3782
 NSUB = 3782
 NSUB = 3782

Ree2 = .5869
 Ree2 = .6370
 Ree2 = .6674
 Ree2 = .6808

NSUB = 1262
 NSUB = 1262
 NSUB = 1262
 NSUB = 1262

Ree2 = .7077
 Ree2 = .8070
 Ree2 = .7824
 Ree2 = .8882

NSUB = 1310
 NSUB = 1310
 NSUB = 1310
 NSUB = 1310

Ree2 = .8727
 Ree2 = .8764
 Ree2 = .9328
 Ree2 = .9460

NSUB = 1239
 NSUB = 1239
 NSUB = 1239
 NSUB = 1239

Ree2 = .7190
 Ree2 = .8665
 Ree2 = .7786
 Ree2 = .8682

NSUB = 1308
 NSUB = 1308
 NSUB = 1308
 NSUB = 1308

Ree2 = .7952
 Ree2 = .8917
 Ree2 = .8386
 Ree2 = .9034

NSUB = 1311
 NSUB = 1311
 NSUB = 1311
 NSUB = 1311

Ree2 = .3173
 Ree2 = .5504
 Ree2 = .3781
 Ree2 = .6063

NSUB = 1301
 NSUB = 1301
 NSUB = 1301
 NSUB = 1301

Ree2 = .7342
 Ree2 = .8634
 Ree2 = .7820
 Ree2 = .8664

NSUB = 1310
 NSUB = 1310
 NSUB = 1310
 NSUB = 1310

Ree2 = .7191
 Ree2 = .8631
 Ree2 = .7468
 Ree2 = .8653

NSUB = 1224
 NSUB = 1224
 NSUB = 1224
 NSUB = 1224

REGRESSION EQUATIONS FOR HIP BREADTH, STANDING

HIP BREADTH, STANDING = .3552E-01*AGE +5.542
 HIP BREADTH, STANDING = .4357E-01*WEIGHT +5.903
 HIP BREADTH, STANDING = .1969 *STANDING -7.718
 HIP BREADTH, STANDING = .1151E-01*AGE +.3192E-01*WEIGHT +.1642E-01*STANDING +5.020
 R₀₀₂ = .8640 NSUB = 1234
 R₀₀₂ = .9229 NSUB = 1234
 R₀₀₂ = .8611 NSUB = 1234
 R₀₀₂ = .9477 NSUB = 1234

REGRESSION EQUATIONS FOR SHOULDER TO ELBOW LENGTH

SHOULDER TO ELBOW = .3933E-01*AGE +6.369
 SHOULDER TO ELBOW = .5175E-01*WEIGHT +7.038
 SHOULDER TO ELBOW = .2237 *STANDING -9.239
 SHOULDER TO ELBOW = .8433E-03*AGE +.2193 *STANDING -7.898
 R₀₀₂ = .8922 NSUB = 3823
 R₀₀₂ = .8440 NSUB = 3823
 R₀₀₂ = .9735 NSUB = 3823
 R₀₀₂ = .9736 NSUB = 3823

REGRESSION EQUATIONS FOR FOREARM-HAND LENGTH

FOREARM-HAND LENGTH = .4900E-01*AGE +8.421
 FOREARM-HAND LENGTH = .6536E-01*WEIGHT +9.182
 FOREARM-HAND LENGTH = .2804 *STANDING -7.587
 FOREARM-HAND LENGTH = -.2689E-02*AGE +.4490E-02*WEIGHT +.2776 *STANDING -6.374
 R₀₀₂ = .8783 NSUB = 3821
 R₀₀₂ = .8541 NSUB = 3821
 R₀₀₂ = .9701 NSUB = 3821
 R₀₀₂ = .9709 NSUB = 3821

REGRESSION EQUATIONS FOR BICEPS CIRCUMFERENCE

BICEPS CIRCUMFERENCE = .2664E-01*AGE +4.976
 BICEPS CIRCUMFERENCE = .4173E-01*WEIGHT +4.878
 BICEPS CIRCUMFERENCE = .1501 *STANDING +1.143
 BICEPS CIRCUMFERENCE = .5211E-01*WEIGHT -.4492E-01*STANDING +6.478
 R₀₀₂ = .6794 NSUB = 3824
 R₀₀₂ = .9115 NSUB = 3824
 R₀₀₂ = .7281 NSUB = 3824
 R₀₀₂ = .9203 NSUB = 3824

REGRESSION EQUATIONS FOR ELBOW CIRCUMFERENCE

ELBOW CIRCUMFERENCE = .2267E-01*AGE +5.152
 ELBOW CIRCUMFERENCE = .3434E-01*WEIGHT +5.166
 ELBOW CIRCUMFERENCE = .1290 *STANDING +.9440
 ELBOW CIRCUMFERENCE = -.1938E-02*AGE +.3358E-01*WEIGHT +.1344E-01*STANDING +4.738
 R₀₀₂ = .7400 NSUB = 3822
 R₀₀₂ = .9287 NSUB = 3822
 R₀₀₂ = .8097 NSUB = 3822
 R₀₀₂ = .9293 NSUB = 3822

REGRESSION EQUATIONS FOR FOREARM CIRCUMFERENCE

FOREARM CIRCUMFERENCE = .2267E-01*AGE +5.152
 FOREARM CIRCUMFERENCE = .3434E-01*WEIGHT +5.166
 FOREARM CIRCUMFERENCE = .1290 *STANDING +.9440
 FOREARM CIRCUMFERENCE = -.1938E-02*AGE +.3358E-01*WEIGHT +.1344E-01*STANDING +4.738
 R₀₀₂ = .7400 NSUB = 3822
 R₀₀₂ = .9287 NSUB = 3822
 R₀₀₂ = .8097 NSUB = 3822
 R₀₀₂ = .9293 NSUB = 3822

REGRESSION EQUATIONS FOR WRIST CIRCUMFERENCE

WRIST CIRCUMFERENCE = .1145E-01*AGE +3.971
 WRIST CIRCUMFERENCE = .1771E-01*WEIGHT +3.951
 WRIST CIRCUMFERENCE = .6620E-01*STANDING +1.791
 WRIST CIRCUMFERENCE = -.3478E-02*AGE +.1804E-01*WEIGHT +.1674E-01*STANDING +3.447
 R₀₀₂ = .6390 NSUB = 1311
 R₀₀₂ = .8395 NSUB = 1311
 R₀₀₂ = .7273 NSUB = 1311
 R₀₀₂ = .8446 NSUB = 1311

REGRESSION EQUATIONS FOR KNEE HEIGHT, SEATED

KNEE HEIGHT, SEATED = .5917E-01*AGE +9.584
 KNEE HEIGHT, SEATED = .7857E-01*WEIGHT +10.55
 KNEE HEIGHT, SEATED = .3433 *STANDING -1.746
 KNEE HEIGHT, SEATED = -.8480E-02*AGE -.4527E-02*WEIGHT +.4045 *STANDING -3.654
 R₀₀₂ = .8612 NSUB = 3678
 R₀₀₂ = .8222 NSUB = 3678
 R₀₀₂ = .9693 NSUB = 3678
 R₀₀₂ = .9714 NSUB = 3678

REGRESSION EQUATIONS FOR THIGH CIRCUMFERENCE

THIGH CIRCUMFERENCE = .6066E-01*AGE +9.311
 THIGH CIRCUMFERENCE = .8944E-01*WEIGHT +9.551
 THIGH CIRCUMFERENCE = .3382 *STANDING -1.560
 THIGH CIRCUMFERENCE = .1018E-01*AGE +.8338E-01*WEIGHT -.2709E-01*STANDING +10.25
 R₀₀₂ = .7556 NSUB = 3782
 R₀₀₂ = .8992 NSUB = 3782
 R₀₀₂ = .7921 NSUB = 3782
 R₀₀₂ = .9015 NSUB = 3782

REGRESSION EQUATIONS FOR UPPER LEG CIRCUMFERENCE
 UPPER LEG CIRCUMF = .4805E-01*AGE +7.998
 UPPER LEG CIRCUMF = .7076E-01*WEIGHT +8.195
 UPPER LEG CIRCUMF = .2691 *STANDING -.6787
 UPPER LEG CIRCUMF = .5930E-02*AGE +.6358E-01*WEIGHT +8.043
 R_{ee2} = .7829 NSUB = 3777
 R_{ee2} = .9292 NSUB = 3777
 R_{ee2} = .8201 NSUB = 3777
 R_{ee2} = .9316 NSUB = 3777

REGRESSION EQUATIONS FOR KNEE CIRCUMFERENCE
 KNEE CIRCUMFERENCE = .4805E-01*AGE +7.998
 KNEE CIRCUMFERENCE = .7076E-01*WEIGHT +8.195
 KNEE CIRCUMFERENCE = .2691 *STANDING -.6787
 KNEE CIRCUMFERENCE = .5930E-02*AGE +.6358E-01*WEIGHT +8.043
 R_{ee2} = .7829 NSUB = 3777
 R_{ee2} = .9292 NSUB = 3777
 R_{ee2} = .8201 NSUB = 3777
 R_{ee2} = .9316 NSUB = 3777

REGRESSION EQUATIONS FOR CALF CIRCUMFERENCE
 CALF CIRCUMFERENCE = .3544E-01*AGE +6.685
 CALF CIRCUMFERENCE = .5209E-01*WEIGHT +6.839
 CALF CIRCUMFERENCE = .1998 *STANDING +.2129
 CALF CIRCUMFERENCE = .1539E-02*AGE +.4370E-01*WEIGHT +.2825E-01*STANDING +5.794
 R_{ee2} = .7907 NSUB = 3822
 R_{ee2} = .9342 NSUB = 3822
 R_{ee2} = .8486 NSUB = 3822
 R_{ee2} = .9380 NSUB = 3822

REGRESSION EQUATIONS FOR ANKLE CIRCUMFERENCE
 ANKLE CIRCUMFERENCE = .1770E-01*AGE +5.116
 ANKLE CIRCUMFERENCE = .2659E-01*WEIGHT +5.152
 ANKLE CIRCUMFERENCE = .1016 *STANDING +1.786
 ANKLE CIRCUMFERENCE = -.3664E-02*AGE +.2284E-01*WEIGHT +.3523E-01*STANDING +3.995
 R_{ee2} = .7020 NSUB = 1314
 R_{ee2} = .8686 NSUB = 1314
 R_{ee2} = .7887 NSUB = 1314
 R_{ee2} = .8741 NSUB = 1314

REGRESSION EQUATIONS FOR ANKLE HEIGHT, OUTSIDE
 ANKLE HEIGHT, OUTSI = .6637E-02*AGE +1.319
 ANKLE HEIGHT, OUTSI = .9232E-02*WEIGHT +1.417
 ANKLE HEIGHT, OUTSI = .4015E-01*STANDING -.2032E-01
 ANKLE HEIGHT, OUTSI = -.1302E-02*AGE +.4697E-01*STANDING -.2305
 R_{ee2} = .5237 NSUB = 1182
 R_{ee2} = .5227 NSUB = 1182
 R_{ee2} = .5974 NSUB = 1182
 R_{ee2} = .5992 NSUB = 1182

REGRESSION EQUATIONS FOR FOOT BREADTH
 FOOT BREADTH = .8742E-02*AGE +2.193
 FOOT BREADTH = .1221E-01*WEIGHT +2.283
 FOOT BREADTH = .5052E-01*STANDING +.5281
 FOOT BREADTH = -.1722E-02*AGE +.4119E-02*WEIGHT +.4407E-01*STANDING +.7576
 R_{ee2} = .7581 NSUB = 3826
 R_{ee2} = .8088 NSUB = 3826
 R_{ee2} = .8544 NSUB = 3826
 R_{ee2} = .8687 NSUB = 3826

REGRESSION EQUATIONS FOR FOOT LENGTH
 FOOT LENGTH = .2436E-01*AGE +5.384
 FOOT LENGTH = .3275E-01*WEIGHT +5.742
 FOOT LENGTH = .1416 *STANDING +.7017
 FOOT LENGTH = -.5757E-02*AGE +.1715 *STANDING -.2125
 R_{ee2} = .8191 NSUB = 3828
 R_{ee2} = .8079 NSUB = 3828
 R_{ee2} = .9341 NSUB = 3828
 R_{ee2} = .9380 NSUB = 3828

APPENDIX E INERTIAL PROPERTIES OF ELLIPSOIDS AND RIGHT ELLIPTICAL CYLINDER STACKS

An ellipsoid with a semiaxis length in the x direction of a, in the y direction of b, and in the z direction of c has volume $4/3 \pi abc$. If this ellipsoid is homogeneous with density ρ its inertial properties are as follows:

$$\begin{aligned} \text{mass} &= 4/3 \pi \rho abc, \\ \text{x moment of inertia} &= \frac{\text{mass}}{5} (b^2 + c^2), \\ \text{y moment of inertia} &= \frac{\text{mass}}{5} (a^2 + c^2), \\ \text{z moment of inertia} &= \frac{\text{mass}}{5} (a^2 + b^2), \end{aligned}$$

and the center of gravity is located at the center of the ellipsoid.

The other geometric model utilized by GEBOD for the determination of inertial properties is a stack of right elliptical cylinders.

The cylinders in the stack are numbered from 1 to n (where there are n cylinders in the stack) sequentially from one end of the stack to the other. In order to locate the center of gravity of this figure an axis system must be defined. The origin of this axis system is located at the center of the elliptical end surface of cylinder 1 most distant from the center of the stack. The x, y, and z axes are parallel to the directions of the local reference system of the segment being modeled (see Section 3). The end of the stack is chosen for the origin (and to begin numbering with) so that the positive z axis passes through all the cylinders.

The cylinders are stacked so that the positive z axis passes through the center of both elliptical end surfaces of each cylinder. The cylinders are oriented so that one semiaxis (referred to as the x semiaxis) is parallel to the x axis, and the other (referred to as the y semiaxis) is parallel to the y axis. The length of the x semiaxis of cylinder i is referred to as a_i , and the length of the y

semiaxis is referred to as b_i . Each cylinder has the same height, called h . By assumption, each cylinder is also homogeneous with density ρ , giving the i^{th} cylinder the following geometric and inertial properties:

$$\begin{aligned}
 \text{volume} &= v_i = \pi a_i b_i h, \\
 \text{mass} &= m_i = \rho v_i, \\
 \text{x moment of inertia} &= I_{xx_i} = \frac{m_i}{12} (3b_i^2 + h^2), \\
 \text{y moment of inertia} &= I_{yy_i} = \frac{m_i}{12} (3a_i^2 + h^2), \\
 \text{z moment of inertia} &= I_{zz_i} = \frac{m_i}{4} (a_i^2 + b_i^2), \\
 \text{x center of mass coordinate} &= cgx_i = 0.0 \\
 \text{y center of mass coordinate} &= cgy_i = 0.0 \\
 \text{z center of mass coordinate} &= cgz_i = (i - \frac{1}{2})h,
 \end{aligned}$$

where the x, y, and z moments of inertia are about axes parallel to the x, y, and z reference axes, respectively, but through the center (both geometric center and center of gravity) of the cylinder.

To compute the mass or volume of the entire stack the individual masses or volumes are summed. The center of mass of the stack is located as follows:

$$\begin{aligned}
 \text{x center of mass coordinate} = cgx &= \frac{\sum m_i cgx_i}{\sum m_i} = 0.0, \\
 \text{y center of mass coordinate} = cgy &= \frac{\sum m_i cgy_i}{\sum m_i} = 0.0, \\
 \text{z center of mass coordinate} = cgz &= \frac{\sum m_i cgz_i}{\sum m_i}.
 \end{aligned}$$

Moments of inertia may be combined by simple summing, as long as they have all been computed relative to the same set of axes. Since different x and y axes have been used in the computation of each cylinder's moments of inertia, a single set of axes must be defined, the individual moments of inertia recomputed relative to that set of axes, and then summed. It is standard to express moments of inertia relative to axes at the center of gravity of a body, and

this is assumed by the ATB Model. For this reason a new axis system is defined at the center of mass of the stack and parallel to the old reference system. Since the x and y coordinates of the center of mass, relative to the old system, are both zero, the new and old systems share a common z axis, which is also the z axis relative to which the I_{zz_i} ($i = 1, n$) were computed. Thus, the moment of inertia of the stack relative to this new z axis is simply the sum of the individual I_{zz_i} . Since the x axes relative to which the I_{xx_i} ($i = 1, n$) were computed are all parallel to the x axis of the new system, the parallel axis theorem may be used to recompute the moments of inertia of each cylinder relative to the new system's x axis, and these values may then be summed. The same procedure is then applied to the moments of inertia about y. These computations which determine the moments of inertia of the entire stack are summarized as follows:

$$\text{x moment of inertia} = I_{xx} = \sum_{i=1}^n [I_{xx_i} + m_i (cgz - cgz_i)^2],$$

$$\text{y moment of inertia} = I_{yy} = \sum_{i=1}^n [I_{yy_i} + m_i (cgz - cgz_i)^2],$$

$$\text{z moment of inertia} = I_{zz} = \sum_{i=1}^n I_{zz_i}.$$

APPENDIX F

SOURCE LISTING OF PROGRAM GEBOD

```

C--PROGRAM GEBOD------(PERKIN-ELMER FTM V11)-----C
C  GEBOD GENERATES BODY DESCRIPTION DATA SETS FOR USE IN THE ARTICULATED C
C  TOTAL BODY (ATB) MODEL.  USER HAS CHOICE OF PRODUCING A DATA SET C
C  CORRESPONDING TO ADULT MALE, ADULT FEMALE, OR A CHILD SUBJECT. C
C  THE BASIC GEOMETRY OF THE MODEL USED TO CALCULATE THE BODY DESCRIPTION C
C  DATA IS AN EXTENSIVELY MODIFIED VERSION OF THE MODEL USED BY C
C  PROGRAM GOOD (GENERATOR OF OCCUPANT DATA) WRITTEN BY CALSPAN C
C  CORP.  THE MODIFICATIONS TO THE MODEL AND THIS THE RESULTING C
C  PROGRAM, WERE WRITTEN BY THE UNIVERSITY OF DAYTON RESEARCH C
C  INSTITUTE UNDER CONTRACT #33615-81-C-0513 C
C
C  FILES: C
C  UNIT1--USER SUPPLIED DIMENSIONAL DATA. C
C  UNIT3--RESULTS READY FOR INSERTION INTO AN ATB MODEL INPUT DECK. C
C  UNIT5 (CRT OUTPUT)--INPUT PROMPTS ARE WRITTEN TO THIS UNIT. C
C  UNIT7 (CRT INPUT)--SUBJECT DESCRIPTION IS ENTERED TO THIS UNIT. C
C  UNIT9 (PRINTER)--TABLE FORM OF RESULTS. C
C
C  ROUTINES (IN ORDER OF APPEARANCE): C
C  PROGRAM GEBOD C
C  BLOCK DATA C
C  SUBROUTINE DIALOG C
C  SUBROUTINE ASKUN C
C  SUBROUTINE PTILE C
C  SUBROUTINE CONTAC C
C  SUBROUTINE SEGMA5 C
C  SUBROUTINE SGINER C
C  SUBROUTINE ELLIP C
C  ENTRY ELLPMI C
C  SUBROUTINE TORSO C
C  SUBROUTINE FEET C
C  SUBROUTINE RESULTS C
C  SUBROUTINE CNVRT C
C-----C
C
C  PROGRAM GEBOD C
C  COMMON /DIMS/ DD(-1:31),REGEQ(24,-1:31),PRED(0:2) C
C  COMMON /FLOAT/ PI,PI2,PI4 C
C
C  CALL CARCCN (9,1) C
C  PI = ACOS(-1.) C
C  PI2 = PI * PI C
C  PI4 = PI2 * PI2 C
C
C 10  CALL DIALOG (IPTR,ICNT,ISTR) C
C     IF (IPTR.LT.25) THEN C
C       DO 100 I = ISTR,31 C
C         DD(I) = REGEQ(IPTR+ICNT,I) C
C       DO 100 J = 0,ICNT -1 C
C         DD(I) = DD(I) + PRED(J)*REGEQ(IPTR+J,I) C
C 100  DD(I) = DD(I) + PRED(J)*REGEQ(IPTR+J,I) C
C
C  ENDIF C
C
C  CALL CONTAC C
C  CALL SEGMA5 C
C  CALL SGINER C
C  CALL RESULTS (ISTR) C
C  GOTO 10 C
C  END C
C-----C
C  --BLOCK DATA-----C
C  DATA IN COMMON AREAS C
C  /SGMNTS/--SEGMENT DATA C

```



```

C      ABCN--X,Y, AND Z CONTACT ELLIPSOID SEMIAXES FOR EACH SEGMENT
C      RMN--MASS OF EACH SEGMENT
C      PHI--SEGMENT MOMENTS OF INERTIA
C      XYZCG--LOCAL REFERENCE COORDINATES OF CENTER OF SEGMENT
C      CONTACT ELLIPSOIDS
C
C      /JNTS/--JOINT DATA
C      RNJ--LOCAL REFERENCE SYSTEM COORDINATES OF EACH JOINT. THIRD
C      SUBSCRIPT EQUAL TO 2 SPECIFIES LOCAL REFERENCE SYSTEM OF SEGMENT
C      J+1. A VALUE OF 1 IN THIS POSITION SPECIFIES LOCAL REFERENCE
C      SYSTEM OF SEGMENT JNT(J), WHERE IN BOTH CASES J IS THE VALUE OF
C      THE FIRST SUBSCRIPT.
C      JNT--POINTER ARRAY FOR ASSOCIATING JOINTS WITH SEGMENTS
C      YPRLL--YAW, PITCH, AND ROLL ANGLES OF JOINT AXES RELATIVE TO LOCAL
C      REFERENCE AXES
C      IPIN--SPECIFIES JOINT TYPE
C
C      /DIMS/--BODY DIMENSION DATA
C      DD--BODY DIMENSIONS
C      REGEQ--REGRESSION EQUATIONS USED TO COMPUTE BODY DIMENSIONS
C      PRED--VALUES OF PREDICTING VARIABLES TO BE USED WITH REGEQ
C      RANGE--ACCEPTIBLE RANGE FOR PREDICTING VARIABLES
C      CONV--CONSTANTS FOR CONVERTING BODY DIMENSIONS FROM METRIC TO
C      ENGLISH UNITS
C
C      /NAMES/--CHARACTER STRINGS FOR VARIOUS LABELS
C      SUBTYP--DESCRIPTION TO USER OF 4 SOURCES OF BODY DIMENSION DATA
C      SEGLAB--SEGMENT LABELS
C      JNTLAB--JOINT LABELS
C      PLTSYM--PLOTING SYMBOL FOR SEGMENTS AND JOINTS
C      DIMLAB--NAMES OF THE BODY DIMENSIONS
C      TITLE--RUN TITLE SUPPLIED BY THE USER
C      UNITS--UNITS FOR USER TO CHOOSE BETWEEN
C
C      /FLOAT/--VARIOUS CONSTANTS
C      PI--THE CONSTANT PI
C      PI2--PI**2
C      PI4--PI**4
C      DENS--DENSITY USED FOR COMPUTATION OF SEGMENT INERTIAL PROPERTIES
C      GRAV--ACCELERATION OF GRAVITY
C
C      /CYL/--DATA USED IN RIGHT ELLIPTICAL CYLINDER MODELLING OF SEGMENTS
C      FOR COMPUTATION OF INERTIAL PROPERTIES
C      ZESS--CONTAINS Z COORDINATE GIVING VERTICAL EXTENT OF CYLINDERS
C      ZH--HEIGHT OF EACH CYLINDER IN THE NUMERICAL INTEGRATION
C      NSEG--NUMBER OF CYLINDERS IN THE NUMERICAL INTEGRATION
C      CGZ--Z COORDINATE OF CENTER OF GRAVITY OF MODEL
C      WTCCR--EIGHT COORECTION FACTOR USED TO ADJUST DENS
C
C      ALL DATA WILL BE CALCULATED AND STORED IN ENGLISH UNITS
C      DD(1)--MONTHS
C      DD(2)--POUNDS
C      DD(3)--INCHES
C      DENS--SLUG/IN**3
C      GRAV--IN/SEC**2
C      RMN--SLUGS
C      PHI--SLUG*IN**2
C      ALL REMAINING LINEAR MEASUREMENTS ARE IN INCHES
C      THESE UNITS ARE UTILIZED UNTIL JUST PRIOR TO WRITTING OUT OF RE-
C      SULTS. VALUES ARE THEN CONVERTED, IN PLACE, TO APPROPRIATE UNITS.
C      THE VALUE STORED IN GRAV IS USED FOR CONVERSION FROM SLUGS TO
C      POUNDS.
C-----

```

```

BLOCK DATA
COMMON /SGMNTS/ ABCN(15),RMN(15),PHI(3,15),XYZCG(15,3)
COMMON /JNTS/ RHJ(3,28),JNT(14),YPRLL(14,6),I*IN(14)
COMMON /DIMS/ DD(-1:31),REGEQ(24,-1:31),PRED(3),
& RANGE(2,-1:1,3),CONV(-1:1)
COMMON /NAMES/ SUBTYP(4),SEGLAB(15),JNTLAB(14),PLTSYM(29),
& DIMLAB(-1:31),TITLE,UNITS(3,-1:2)
COMMON /FLOAT/ PI,PI2,PI4,DENS,GRAV
COMMON /CYL/ ZEES(0:15),ZH(15),NSEG(15),CGZ(15),WTCCR
CHARACTER SUBTYP*20,SEGLAB*3,JNTLAB*2,PLTSYM*1,DIMLAB*24,TITLE*60
CHARACTER UNITS*6

```

```

DATA SEGLAB/'LT','CT','UT','N','H','RUL','RLL',
& 'RF','LUL','LLL','LF','RUA','RLA','LUA','LLA',
DATA JNTLAB/'P','W','NP','MP','RH','RK','RA',
& 'LH','LK','LA','RS','RE','LS','LE',
DATA PLTSYM/'1','2','3','4','5','6','7','8','9','A','B','C','D',
& 'E','F','M','N','O','P','Q','R','S','T','U','V','W','X','Y','Z',
DATA JNT/1,2,3,4,1,6,7,1,9,10,3,12,3,14,
DATA SUBTYP/'CHILD (2 - 19 YEARS)','ADULT FEMALE',
& 'ADULT MALE','USER SUPPLIED DIM.',
DATA UNITS/'MONTHS','YEARS','','LBS','KGRAMS','X-TILE',
& 'IN','CM','X-TILE','ENGLISH','METRIC',' ',
DATA CONV/12.,2.2046.,39370./,DENS,GRAV/1.12287E-3,32.17405/

```

C

C DIMENSIONAL DATA LABELS

```

DATA DIMLAB /
& 'AGE' 'WEIGHT'
& 'STANDING HEIGHT' 'SHOULDER HEIGHT'
& 'ARMPIT HEIGHT' 'WAIST HEIGHT'
& 'SEATED HEIGHT' 'HEAD LENGTH'
& 'HEAD BREADTH' 'HEAD TO CHIN HEIGHT'
& 'NECK CIRCUMFERENCE' 'SHOULDER BREADTH'
& 'CHEST DEPTH' 'CHEST BREADTH'
& 'WAIST DEPTH' 'WAIST BREADTH'
& 'BUTTOCK DEPTH' 'HIP BREADTH,STANDING'
& 'SHOULDER TO ELBOW LENGTH' 'FOREARM-HAND LENGTH'
& 'BICEPS CIRCUMFERENCE' 'ELBOW CIRCUMFERENCE'
& 'FOREARM CIRCUMFERENCE' 'WRIST CIRCUMFERENCE'
& 'KNEE HEIGHT,SEATED' 'THIGH CIRCUMFERENCE'
& 'UPPER LEG CIRCUMFERENCE' 'KNEE CIRCUMFERENCE'
& 'CALF CIRCUMFERENCE' 'ANKLE CIRCUMFERENCE'
& 'ANKLE HEIGHT,OUTSIDE' 'FOOT BREADTH'
& 'FOOT LENGTH'
DATA RANGE /
& 24.00 / 240.0 / 22.27 / 247.6 / 32.01 / 76.54 /
& 18.50 / 56.50 / 83.00 / 200.0 / 56.93 / 72.03 /
& 21.50 / 50.50 / 118.0 / 264.0 / 62.17 / 77.64 /
DATA (REGEQ(J,-1), J=1,24) /
& 1.000 / .4547E-12, 1.213 / 25.43 / 5.202 / -158.9 /
& 1.000 / 0. / 0. / .4547E-12, 0. / 0. /
& 0. / 0. / 0. / 0. / 0. / 0. /
& 0. / 0. / 0. / 0. / 0. / 0. /
DATA (REGEQ(J, 0), J=1,24) /
& .6625 / -.7660 / 1.000 / .4547E-12, 3.743 / -122.2 /
& 20. / 1.000 / 0. / .4547E-12, 1.000 / .4547E-12,
& 3.737 / -111.2 / 1.000 / 0. / .4547E-12, 1.000 /
& .9095E-12, 4.530 / -142.7 / 1.000 / 0. / .9095E-12/
DATA (REGEQ(J, 1), J=1,24) /
& .1756 / 32.62 / .2314 / 35.58 / 1.000 / .2274E-12,
& 40. / 0. / 1.000 / .2274E-12, .7589E-01, 54.16 /
& 1.000 / .2274E-12, 0. / 1.000 / .2274E-12, .5850E-01,

```

```

2 59.56 / 1.000 / .4547E-12,0. / 1.000 / .4547E-12/
DATA (REGEQ(J, 2), J=1,24) /
1 .1518 / 24.79 / .1994 / 27.37 / .8721 / -3.398 /
80. / 0. / .8721 / -3.398 / .7182E-01 / 42.77 /
& .8731 / -3.936 / .7555E-02 / .3469 / -3.096 / .5344E-01 /
& 47.02 / .8911 / -5.049 / .8583E-02 / .8522 / -3.824 /
DATA (REGEQ(J, 3), J=1,24) /
1 .1467 / 22.53 / .1916 / 25.19 / .8315 / -4.469 /
80. / -.1217E-01 / .8770 / -5.954 / .5840E-01 / 39.83 /
& .8309 / -5.762 / -.6495E-02 / .8551 / -6.484 / .4637E-01 /
& 43.06 / .8398 / -7.529 / -.3761E-02 / .8569 / -8.066 /
DATA (REGEQ(J, 4), J=1,24) /
1 .1186 / 17.74 / .1530 / 19.97 / .6922 / -4.726 /
30. / -.1855E-01 / .7519 / -7.012 / .5302E-01 / 32.73 /
& .6845 / -4.206 / 0. / .6845 / -4.206 / .3642E-01 /
& 35.39 / .7043 / -7.256 / -.6506E-02 / .7338 / -5.185 /
DATA (REGEQ(J, 5), J=1,24) /
1 .7804E-01 / 19.17 / .1047 / 20.34 / .4412 / 4.849 /
& .5848E-02 / .1910E-01 / .3393 / 8.114 / .3620E-01 / 29.09 /
& .4225 / 6.734 / .5773E-02 / .4010 / 7.376 / .2664E-01 /
& 32.06 / .4043 / 8.460 / .4060E-02 / .3859 / 9.039 /
DATA (REGEQ(J, 6), J=1,24) /
& .3642E-02 / 6.881 / .5571E-02 / 6.881 / .2249E-01 / 6.110 /
3-.3975E-02 / .2793E-02 / .3264E-01 / 5.825 / .4897E-02 / 6.625 /
5.3600E-01 / 4.930 / .3021E-02 / .2471E-01 / 5.296 / .3209E-02 /
& 7.266 / .2680E-01 / 5.952 / .2233E-02 / .1668E-01 / 6.271 /
DATA (REGEQ(J, 7), J=1,24) /
1 .3642E-02 / 5.220 / .5337E-02 / 5.237 / .2096E-01 / 4.532 /
& -.6471E-03 / .3641E-02 / .1071E-01 / 4.873 / .4089E-02 / 5.194 /
& .1347E-01 / 4.855 / .4089E-02,0. / 5.194 / .3060E-02 /
& 5.611 / .1174E-01 / 5.322 / .3060E-02,0. / 5.611 /
DATA (REGEQ(J, 8), J=1,24) /
& .8988E-02 / 6.582 / .1266E-01 / 6.666 / .5203E-01 / 4.867 /
& -.2157E-02 / .4530E-02 / .4621E-01 / 5.080 / .7362E-02 / 7.688 /
& .6816E-01 / 4.275 / .3057E-02 / .5674E-01 / 4.615 / .3143E-02 /
& 8.420 / .4659E-01 / 5.712 / 0. / .4659E-01 / 5.712 /
DATA (REGEQ(J, 9), J=1,24) /
& .2281E-01 / 8.421 / .3449E-01 / 8.448 / .1301 / 4.177 /
& -.2812E-02 / .3292E-01 / .2141E-01 / 7.760 / .2316E-01 / 10.34 /
& .8900E-01 / 7.607 / .2316E-01,0. / 10.34 / .2444E-01 /
& 10.85 / .6527E-01 / 10.54 / .2806E-01 / -.6185E-01 / 14.54 /
DATA (REGEQ(J,10), J=1,24) /
& .3595E-01 / 7.530 / .4866E-01 / 8.020 / .2040 / .8749 /
& .4037E-02 / .1483E-01 / .1271 / 3.354 / .1927E-01 / 11.66 /
& .1246 / 6.160 / .1369E-01 / .7344E-01 / 7.682 / .1612E-01 /
& 13.24 / .1181 / 7.790 / .1253E-01 / .6133E-01 / 9.578 /
DATA (REGEQ(J,11), J=1,24) /
& .2870E-01 / 5.225 / .4249E-01 / 5.333 / .1620 / -.2418E-01 /
30. / .3764E-01 / .2091E-01 / 4.589 / .3412E-01 / 4.965 /
& .7300E-01 / 4.650 / .3989E-01 / -.7607E-01 / 9.086 / .2690E-01 /
& 4.984 / .6114E-01 / 5.386 / .3174E-01 / -.8265E-01 / 9.915 /
DATA (REGEQ(J,12), J=1,24) /
& .2699E-01 / 5.195 / .3856E-01 / 5.411 / .1504 / .3666 /
& .4513E-02 / .2798E-01 / .2213E-01 / 4.506 / .3185E-01 / 6.968 /
& .8875E-01 / 5.357 / .3505E-01 / -.4222E-01 / 9.255 / .2911E-01 /
& 7.854 / .8877E-01 / 6.709 / .3254E-01 / -.5866E-01 / 11.35 /
DATA (REGEQ(J,13), J=1,24) /
& .1284E-01 / 5.024 / .2279E-01 / 4.763 / .7598E-01 / 2.485 /
& -.8176E-02 / .3995E-01 / -.3147E-01 / 6.097 / .2922E-01 / 2.979 /
& .5358E-01 / 3.279 / .3511E-01 / -.7761E-01 / 7.183 / .3026E-01 /
& 3.528 / .5167E-01 / 5.174 / .3706E-01 / -.1162 / 10.46 /
DATA (REGEQ(J,14), J=1,24) /
& .2718E-01 / 5.367 / .3977E-01 / 5.508 / .1522 / .4650 /

```

```

3 .3925E-02, .3503E-01, 0. , 5.406 , .3527E-01, 5.010 ,
6 .1C60 , 2.734 , .3800E-01, -.3598E-01, 6.959 , .3741E-01,
8 5.694 , .1105 , 4.473 , .4211E-01, -.8025E-01, 10.48 /
DATA (REGEQ(J,15), J=1,24) /
8 .2730E-01, 4.812 , .4032E-01, 4.910 , .1528 , -.1220 ,
6 .4893E-02, .3874E-01, -.1900E-01, 5.466 , .3419E-01, 3.976 ,
3 .7090E-01, 3.803 , .4021E-01, -.7937E-01, 8.275 , .3077E-01,
8 4.095 , .6978E-01, 4.566 , .3632E-01, -.9475E-01, 9.749 /
DATA (REGEQ(J,16), J=1,24) /
8 .3552E-01, 5.542 , .4957E-01, 5.905 , .1968 , -.7718 ,
6 .1151E-01, .3192E-01, .1642E-01, 5.020 , .4052E-01, 8.610 ,
8 .1285 , 5.563 , .4294E-01, -.3192E-01, 10.34 , .2903E-01,
3 9.019 , .1258 , 5.100 , .2903E-01, 0. , 9.019 /
DATA (REGEQ(J,17), J=1,24) /
8 .3933E-01, 6.369 , .5175E-01, 7.038 , .2237 , -.9239 ,
8 .8433E-03, 0. , .2193 , -.7898 , .1702E-01, 10.04 ,
8 .1962 , -.3163 , .2976E-02, .1851 , .1459E-01, .1256E-01,
3 11.97 , .2087 , -.4158 , 0. , .2087 , -.4158 /
DATA (REGEQ(J,18), J=1,24) /
8 .4900E-01, 8.421 , .6536E-01, 9.182 , .2804 , -.7587 ,
8 -.2689E-02, .4490E-02, .2776 , -.6374 , .2092E-01, 13.78 ,
3 .2479 , .6324 , .2960E-02, .2367 , .9615 , .1671E-01,
8 16.54 , .2646 , .9735 , .1677E-02, .2570 , 1.213 /
DATA (REGEQ(J,19), J=1,24) /
8 .2664E-01, 4.976 , .4173E-01, 4.878 , .1501 , .1143 ,
3 0. , .5211E-01, -.4492E-01, 6.478 , .4369E-01, 4.522 ,
8 .5386E-01, 6.646 , .5528E-01, -.1527 , 12.79 , .3340E-01,
8 6.608 , .5996E-01, 8.219 , .4067E-01, -.1243 , 14.02 /
DATA (REGEQ(J,20), J=1,24) /
8 .2267E-01, 5.152 , .3434E-01, 5.166 , .1290 , .9440 ,
8 -.1938E-02, .3358E-01, .1344E-01, 4.738 , .2421E-01, 7.539 ,
8 .1221 , 2.826 , .2086E-01, .4420E-01, 5.145 , .1919E-01,
8 8.767 , .1061 , 4.894 , .1767E-01, .2601E-01, 7.416 /
DATA (REGEQ(J,21), J=1,24) /
8 .2267E-01, 5.152 , .3434E-01, 5.166 , .1290 , .9440 ,
8 -.1938E-02, .3358E-01, .1344E-01, 4.738 , .2643E-01, 5.879 ,
8 .7088E-01, 4.719 , .2938E-01, -.3890E-01, 7.986 , .2116E-01,
8 7.411 , .6768E-01, 6.359 , .2341E-01, -.3835E-01, 9.700 /
DATA (REGEQ(J,22), J=1,24) /
3 .1143E-01, 3.971 , .1771E-01, 3.951 , .6620E-01, 1.791 ,
8 -.3479E-02, .1804E-01, .1674E-01, 3.447 , .1090E-01, 4.503 ,
3 .5371E-01, 2.463 , .9530E-02, .1810E-01, 3.523 , .9921E-02,
8 5.202 , .5166E-01, 3.317 , .9386E-02, .9137E-02, 4.657 /
DATA (REGEQ(J,23), J=1,24) /
8 .5917E-01, 9.584 , .7857E-01, 10.55 , .3433 , -1.746 ,
8 -.8480E-02, -.4527E-02, .4045 , -3.654 , .3002E-01, 14.98 ,
3 .3345 , -2.547 , .6469E-02, .3104 , -1.829 , .2467E-01,
8 17.67 , .3558 , -2.389 , .5244E-02, .3321 , -2.141 /
DATA (REGEQ(J,24), J=1,24) /
8 .6066E-01, 9.311 , .8944E-01, 9.551 , .3322 , -1.560 ,
3 .1018E-01, .8338E-01, -.2709E-01, 10.25 , .8417E-01, 11.13 ,
3 .1869 , 9.912 , .9769E-01, -.1781 , 20.77 , .6998E-01,
3 11.01 , .1614 , 11.89 , .8237E-01, -.2117 , 23.64 /
DATA (REGEQ(J,25), J=1,24) /
8 .4805E-01, 7.998 , .7076E-01, 8.195 , .2691 , -.6787 ,
8 .5930E-02, .6358E-01, 0. , 8.043 , .6412E-01, 9.905 ,
8 .1664 , 7.448 , .7187E-01, -.1022 , 15.44 , .3229E-01,
3 9.621 , .1412 , 5.370 , .3229E-01, 0. , 9.621 /
DATA (REGEQ(J,26), J=1,24) /
8 .4805E-01, 7.998 , .7076E-01, 8.195 , .2691 , -.6787 ,
8 .5930E-02, .6358E-01, 0. , 8.043 , .4406E-01, 3.694 ,
8 .1458 , 4.985 , .4605E-01, -.2626E-01, 10.11 , .3334E-01,
8 9.686 , .1512 , 4.916 , .3334E-01, 0. , 9.686 /

```

```

DATA (REGEQ(J,27), J=1,24) /
1 .3544E-01, 6.685, .5209E-01, 6.639, .1998, .2129,
2 .1539E-02, .4370E-01, .2325E-01, 5.794, .4012E-01, 8.335,
3 .1106, 6.386, .4429E-01, .5493E-01, 11.31, .3250E-01,
4 9.002, .8942E-01, 8.469, .3718E-01, .8000E-01, 13.77 /
DATA (REGEQ(J,28), J=1,24) /
5 .1770E-01, 5.116, .2659E-01, 5.152, .1016, 1.786,
6 .3664E-02, .2284E-01, .3523E-01, 3.995, .1809E-01, 3.999,
7 .7603E-01, 3.449, .1720E-01, .1177E-01, 5.361, .1610E-01,
8 6.028, .6599E-01, 4.216, .1665E-01, .9456E-02, 6.593 /
DATA (REGEQ(J,29), J=1,24) /
9 .6837E-02, 1.319, .9232E-02, 1.417, .4015E-01, .2052E-01,
10 .1302E-02, 0., .4697E-01, .2305, .3434E-02, 2.230,
11 .4163E-01, .9788E-02, 0., .4163E-01, .9788E-02, .4310E-02,
12 4.652, .8736E-01, .6990, .1090E-02, .9230E-01, .8545 /
DATA (REGEQ(J,30), J=1,24) /
13 .8742E-02, 2.193, .1221E-01, 2.283, .5052E-01, .5281,
14 .1722E-02, .4119E-02, .4407E-01, .7576, .4638E-02, 2.901,
15 .2947E-01, 1.611, .3353E-02, .1694E-01, 1.984, .4136E-02,
16 3.127, .3418E-01, 1.459, .2907E-02, .2101E-01, 1.873 /
DATA (REGEQ(J,31), J=1,24) /
17 .2436E-01, 5.384, .3275E-01, 5.742, .1416, .7017,
18 .5737E-02, 0., .1715, .2125, .1365E-01, 7.738,
19 .1299, 1.186, .5296E-02, .1101, 1.775, .1029E-01,
20 8.658, .1309, 1.502, .3570E-02, .1148, 2.012 /

```

C

C YAW,PITCH AND ROLL

```

DATA YPRLL/
1 14*0.,30.,0.,0.,30.,0.,90.,45.,0.,90.,45.,0.,60.,0.,60.,
2 32*0.,-90.,-45.,-90.,-90.,-45.,-90.,15.,0.,15.,15*0./
DATA IPIN/C,0,0,0,0,1,0,0,1,0,0,1,0,1/
END

```

```

C--SUBROUTINE DIALOG-----C
C DIALOG WRITES PROMPTS TO THE CRT AND ACCEPTS INPUT FROM THE CRT C
C DESCRIBING THE SUBJECT FOR WHICH BODY DESCRIPTION DATA IS TO BE C
C PRODUCED. THE PARAMETERS, IPTR, ICNT, AND ISTRT, ARE RETURNED TO THE C
C MAIN ROUTINE SPECIFYING THE CHOICES MADE BY THE USER C
C IPTR--SPECIFIES ROW OF REGEQ CONTAINING FIRST REGRESSION EQUATION C
C COEFFICIENT TO BE USED. IPTR IS SET TO 25 FOR USER SUPPLIED C
C DIMENSIONAL DATA. C
C ICNT--NUMBER OF COEFFICIENTS IN THE REGRESSION EQUATION TO BE USED. C
C ISTRT--FIRST BODY DIMENSION TO BE GENERATED: C
C ISTRT =-1 (AGE) FOR CHILD SUBJECTS C
C ISTRT =0 (WEIGHT) FOR ADULT SUBJECTS OR USER SUPPLIED DATA C
C VALUES ARE ALSO READ INTO PRED FOR THE PREDICTING VARIABLES C
C-----C

```

```

SUBROUTINE DIALOG (IPTR,ICNT,ISTRT)
COMMON /DI*3/ DU(-1:31),REGEQ(24,-1:31),PRED(-1:1),
1 RANGE(2,-1:1,3),CCNV(-1:1)
COMMON /NAME*3/ SUBTYP(4),SEGLAB(15),JNTLAB(14),PLTSYM(29),
2 DIMNM(-1:31),TITLE,UNITS(3,-1:2)
CHARACTER SUBTYP*20,SEGLAB*3,JNTLAB*2,PLTSYM*1,ANS*1,DIMNM*24
CHARACTER TITLE*60,UNITS*6,CLR(7)*4
INTEGER IPTMAT(-1:2,3),IPT2(13)
EQUIVALENCE (IPTMAT,IPT2)
DATA IPT2 /1,3,5,7,11,11,13,15,18,18,20,22,25/
DATA CLR /Z185B3F32,26C184818,24A183C0C,Z00194800,3*Z0/

```

```

WRITE (5,11) CLR
WRITE (5,22)
READ (7,333) TITLE
WRITE (5,11) CLR

```

```

WRITE (5,333) ' '//TITLE
WRITE (9,333) '1'//TITLE

10  WRITE (5,33) (I,SUBTYP(I),I=1,4)
    WRITE (5,44)
    READ (7,222) ISUB
    IF (ISUB.GT.4 .OR. ISUB.LT.1) GOTO 10
    WRITE (9,333) '0'//SUBTYP(ISUB)
    ISTRT = -1
    IF (ISUB.GT.1) ISTRT = 0
    IF (ISUB.GT.3) GOTO 100

    WRITE (5,11) CLR
    WRITE (5,333) ' '//TITLE
20  WRITE (5,33) (I+1,DIMNM(I),I=ISTRT,1),3,'ALL OF THE ABOVE'
    WRITE (5,55)
    READ (7,222) IDIM
    IDIM = IDIM -1
    IF (IDIM.LT.ISTRT .OR. IDIM.GT.2) GOTO 20
    IF (IDIM.GE.2) THEN
        LPSTRT = ISTRT
        LPEND = 1
    ELSE
        LPSTRT = IDIM
        LPEND = LPSTRT
    ENDIF

    WRITE (5,11) CLR
    WRITE (5,333) ' '//TITLE
    WRITE (9,555)
    DO 50 I = LPSTRT,LPEND
        CALL ASKUN (DIMNM(I),UNITS(1,I),ICHOS,ISTRT+3)
        IF (ICHOS.GE.3) THEN
            CALL PTILE (ISUB,I,PRED(I))
        ELSE
            TCONV = 1.
            IF (ICHOS.GE.2) TCONV = CONV(I)
40      WRITE (5,77) DIMNM(I),(RANGE(J,I,ISUB)/TCONV,J=1,2)
            READ (5,444) PRED(I)
            WRITE (9,666) DIMNM(I),PRED(I),UNITS(ICHOS,I)
            PRED(I) = PRED(I)*TCONV
            IF ((PRED(I)-RANGE(1,I,ISUB))+(PRED(I)-RANGE(2,I,ISUB))
2          .GT. 0.) GOTO 40
        ENDIF
50    CONTINUE

    IF (IDIM.LT.2) THEN
        PRED(-1) = PRED(IDIM)
    ELSE
        IF (ISUB.GT.1) THEN
            DO 60 I=-1,0
                PRED(I) = PRED(I+1)
60      ENDIF
    ENDIF
    IPTR = IPTMAT(IDIM,ISUB)
    ICNT = IPTMAT(IDIM+1,ISUB) - IPTR - 1
    WRITE (5,11) CLR
    WRITE (5,333) ' '//TITLE
    RETURN

100  WRITE (5,88)
    READ (7,333) ANS
    IF (ANS.EQ.'N') STOP 'FROM DIALOG'

```

```

      IF (ANS.NE.'Y') GOTO 100
      READ (1,99) (DD(I),I=0,31)
      IPTB = 25
      CALL ASKUN(SUBTYP(4),UNITS(1,2),ICHOS,2)
      IF (ICHOS.GE.2) THEN
        DD(0) = DD(0)+CONV(0)
        DO 120 I=1,31
120      DD(I) = DD(I)+CONV(1)
      ENDIF
      RETURN

11      FORMAT (7A4)
22      FORMAT (' PROGRAM GEBOD/' ' GEBOD GENERATES BODY DESCRIPTION',
      &      ' DATA/' ' SUITABLE FOR INPUT TO THE ATB MODEL' /
      &      ' PLEASE ENTER A DESCRIPTION OF THE SUBJECT' ,
      &      ' (<60 CHARS.)' )
33      FORMAT (/(I12,' '),5X,A/)
44      FORMAT (' ENTER NUMBER CORRESPONDING TO DESIRED SUBJECT TYPE')
55      FORMAT (' ENTER NUMBER CORRESPONDING TO '/' PREDICTING',
      &      ' DIMENSION(S) TO BE SUPPLIED')
77      FORMAT (' ENTER VALUE FOR 'A24/' IN THE RANGE 'G10.4',' ',G10.4)
88      FORMAT (' TO UTILIZE EXTERNAL DIMENSIONAL DATA, THE DATA MUST BE'
      &      ' IN THE PROPER FORMAT AND IN A FILE ASSIGNED TO UNIT 1' /
      &      ' HAS THE ABOVE BEEN SATISFIED (Y/N) ?')
99      FORMAT (8F10.0)
222     FORMAT (BN,I60)
333     FORMAT (A)
444     FORMAT (G60.0)
555     FORMAT ('QSELECTED BODY DIMENSIONS' /)
666     FORMAT (A40,G15.4,A6)
      END

C--SUBROUTINE ASKUN-----C
C  ASKUN ASKS USER CHOICE OF UNITS TO BE USED WITH SOME INPUT VARIABLE  C
C  OR THE OUTPUT OF RESULTS.  THE PARAMETERS ARE THE FOLLOWING:         C
C  VARS--CHARACTER STRING DESCRIBING WHAT UNITS ARE TO BE SELECTED FOR  C
C  UNITS--UNITS AVAILABLE TO CHOOSE FROM                                C
C  ICHOS--RETURNS WHICH OF THE UNITS WAS CHOSEN                         C
C  ICNT--NUMBER OF DIFFERENT UNITS AVAILABLE TO CHOOSE FROM             C
C-----C

      SUBROUTINE ASKUN (VARS,UNITS,ICHOS,ICNT)
      CHARACTER VARB*(*) ,UNITS(ICNT)*6,UNITIN*6

30      WRITE (5,66) VARB
      WRITE (5,55) (I,UNITS(I),I=1,ICNT)
      READ (7,44) ICHOS
      IF ( (ICHOS-1)*(ICHOS-ICNT) .GT. 0) GOTO 30

      RETURN
44      FORMAT (BN,I60)
55      FORMAT (I10,' '),5X,A)
66      FORMAT (' SELECT UNITS FOR ',A)
      END

C--SUBROUTINE PTILE-----C
C  PTILE COMPUTES A PERCENTILE POINT, SPECIFIED BY THE USER, OF A BODY  C
C  DIMENSION USED AS A PREDICTOR, BY ASSUMING THE DIMENSION IS          C
C  NORMALLY DISTRIBUTED.  THE PARAMETERS ARE THE FOLLOWING:             C
C  ISUB--SPECIFIES SUBJECT TYPE, AND THUS WHICH POSITION OF THE          C
C  MEAN AND STANDARD ARRAYS TO USE.                                     C
C  IDIM--THE DIMENSION A PERCENTILE POINT IS TO BE COMPUTED FOR         C
C  PRED--RETURNS THE COMPUTED PERCENTILE POINT                          C
C  NOTE: THIS ROUTINE REQUIRES USE OF IMSL ROUTINE MDNRIS                C
C-----C

```

```

SUBROUTINE PFILE (ISUB, IDIM, PRED)
COMMON /NAMES/ SUBTYP(4), SEGLAB(15), JNTLAB(14), PLTSYM(29),
4 DIMNM(-1:31), TITLE, UNITS(3,-1:1)
REAL MEAN(0:1,2:3), STDEV(0:1,2:3)
CHARACTER SUBTYP*20, SEGLAB*3, JNTLAB*2, PLTSYM*1, DIMNM*24
CHARACTER TITLE*60, UNITS*6
DATA MEAN, STDEV/127.24, 63.82, 173.54, 69.82, 16.57, 2.36, 21.42, 2.44/

10 WRITE (5,111) DIMNM(IDIM)
READ (7,99) PCENT
IF ( (PCENT-1.)*(PCENT-100.) .GE. 0.) GOTO 10
WRITE (9,222) DIMNM(IDIM), PCENT
PCENT = PCENT/100.

CALL NOTRI (PCENT, X, D, IER)
PRED = MEAN(IDIM, ISUB) + X*STDEV(IDIM, ISUB)

RETURN
99 FORMAT (F40.0)
111 FORMAT (' ENTER DESIRED PERCENTILE FOR ', A/
8 ' (A REAL VALUE BETWEEN 0. AND 100.)')
222 FORMAT (A40, G15.4, 'X-TILE')
END
C--SUBROUTINE NOTRI-----C
C NOTRI COMPUTES X (THE OUTPUT ARGUMENT SUCH THAT P=Y=THE C
C PROBABILITY THAT U, THE RANDOM VARIABLE, IS LESS THAN OR EQUAL C
C TO X.), D (THE OUTPUT DENSITY, F(X).), AND IER (THE OUTPUT C
C ERROR CODE.) USING P (THE INPUT PROBABILITY.). C
C-----C

SUBROUTINE NOTRI(P, X, D, IE)
C
IE=0
X=.999999E+74
D=X
IF(P)1,4,2
1 IE=-1
GO TO 12
2 IF (P-1.0)7,5,1
4 X=-.999999E+74
5 D=0.0
GO TO 12
C
7 D=P
IF(D-0.5)9,9,8
8 D=1.0-D
9 T2=ALOG(1.0/(D+D))
T=SQR(T2)
X=T*(2.515517+0.802853*T+0.010328*T2)/(1.0+1.432798*T+0.189269*T2
8 +0.001308*T*T2)
IF(P-0.5)10,10,11
10 X=-X
11 D=0.3989423*EXP(-X*X/2.0)
12 RETURN
END
C--SUBROUTINE CONTAC-----C
C CONTAC COMPUTES JOINT LOCATIONS AND CONTACT ELLIPSOID SEMIAXES. C
C-----C

SUBROUTINE CONTAC
COMMON /FLOAT/ PI, PI2, PI4
COMMON /SGHNTS/ AN(15), BN(15), CN(15), RMN(15), PHI(3,15), XYZCG(15,3)

```



```

COMMON /JNTS/ RNJ(3,28)
COMMON /DIMS/ DD(-1:31)

C   THE CENTERS OF GRAVITY AND JOINT X,Y COORDINATES ARE ALL SET TO ZERO.
DO 10 J=1,3
DO 10 I=1,15
10 XYZCG(I,J)=0.0
DO 20 J=1,2
DO 20 I=1,22
20 RNJ(J,I)=0.0

C   NON-ZERO X,Y JOINT COORDINATES ARE COMPUTED.
RNJ(1,21)=DD(29)*0.5
RNJ(1,24)=RNJ(1,21)
RNJ(2,5)=0.5*(DD(16)-DD(24)/PI)
RNJ(2,8)=-RNJ(2,5)
RNJ(2,11)=0.5*(DD(10)-DD(19)/PI)
RNJ(2,13)=-RNJ(2,11)

C   SMW IS ONE HALF THE HEIGHT OF THE ABDOMEN SEGMENT.
C   OLAP IS USED AS AN OVERLAP AMOUNT BETWEEN CERTAIN CONTACT ELLIPSOIDS.
SMW = (DD(2) - DD(4))/10.
OLAP = DD(9)/PI

C   Z COORDINATES OF JOINTS ARE COMPUTED RELATIVE TO SEGMENT JNT(J),
C   WHERE J IS THE SECOND SUBSCRIPT OF RNJ
RNJ(3,1) = (DD(1) - DD(5) - DD(4) + SMW)/2.
RNJ(3,2) = -SMW
RNJ(3,3) = -9.*SMW/2.
RNJ(3,4) = (DD(8) + DD(2) - DD(1) + OLAP/2.)/2.
RNJ(3,5) = (DD(4) - SMW - DD(1) + DD(5) - DD(24)/PI)/2.
RNJ(3,6)=0.5*(DD(1)-DD(5)-DD(23)+DD(24)/PI)
RNJ(3,7)=0.5*(DD(23)-DD(29)-DD(28)/PI2)
RNJ(3,8) = RNJ(3,5)
RNJ(3,9)=RNJ(3,6)
RNJ(3,10)=RNJ(3,7)
RNJ(3,11)=-DD(2)+DD(3)+DD(19)/PI2
RNJ(3,12)=0.5*(DD(17)-DD(20)/PI)
RNJ(3,13)=RNJ(3,11)
RNJ(3,14)=RNJ(3,12)

C   Z COORDINATES OF JOINTS ARE COMPUTED RELATIVE TO SEGMENT J-13,
C   WHERE J IS THE SECOND SUBSCRIPT OF RNJ
RNJ(3,15) = SMW
RNJ(3,16) = -RNJ(3,3)
RNJ(3,17) = (DD(1) - DD(8) - DD(2) - OLAP/2.)/2.
RNJ(3,18) = DD(8) /2. + OLAP/4.
RNJ(3,19)=0.5*(-DD(1)+DD(5)+DD(23)-DD(26)/PI)
RNJ(3,20) = (DD(29) - DD(23) - DD(28)/PI2 + DD(25)/PI)/2.
RNJ(3,21) = DD(29)/PI2 - DD(31)/2.
RNJ(3,22)=RNJ(3,19)
RNJ(3,23)=RNJ(3,20)
RNJ(3,24)=RNJ(3,21)
RNJ(3,25)=0.5*(DD(19)/PI-DD(17))
RNJ(3,26)=0.5*(DD(20)/PI-DD(18))
RNJ(3,27)=RNJ(3,25)
RNJ(3,28)=RNJ(3,26)

C   SEGMENT CONTACT ELLIPSOID X SEMIAXES ARE COMPUTED.
AN(5)=DD(6)*0.5
AN(4)=DD(9)/PI2
AN(3)=DD(11)*0.5
AN(2)=DD(13)*0.5

```

```

AN(1)=DD(15)*0.5
AN(6)=(DD(24)+DD(25))/PI4
AN(7)=DD(27)/PI2
AN(8)=DD(29)*0.5
AN(9)=AN(6)
AN(10)=AN(7)
AN(11)=AN(8)
AN(12)=DD(19)/PI2
AN(13)=DD(21)/PI2
AN(14)=AN(12)
AN(15)=AN(13)

C   SEGMENT CONTACT ELLIPSOID Y SEMIAXES ARE COMPUTED.
BN(5)=DD(7)*0.5
BN(4)=AN(4)
BN(3)=DD(12)*0.5
BN(2)=DD(14)*0.5
BN(1)=DD(16)*0.5
BN(6)=AN(6)
BN(7)=AN(7)
BN(8)=DD(30)*0.5
BN(9)=AN(9)
BN(10)=AN(10)
BN(11)=BN(8)
BN(12)=AN(12)
BN(13)=AN(13)
BN(14)=AN(14)
BN(15)=AN(15)

C   SEGMENT CONTACT ELLIPSOID Z SEMIAXES ARE COMPUTED.
CN(5) = (DD(8) + OLAP/2.)/2.
CN(4) = (DD(1) - DD(8) - DD(2) + OLAP/2.)/2.
CN(3) = 9.*SMW/2.
CN(2) = SMW + OLAP/2.
CN(1) = (DD(4)+DD(5)-DD(1) - SMW)*0.5
CN(6)=(DD(1)-DD(5)-DD(23)+DD(24)/PI+DD(26)/PI)*0.5
CN(7)=(DD(23)-DD(29)+DD(28)/PI2)*0.5
CN(8)=DD(31)*0.5
CN(9)=CN(6)
CN(10)=CN(7)
CN(11)=CN(8)
CN(12)=DD(17)*0.5
CN(13)=DD(18)*0.5
CN(14)=CN(12)
CN(15)=CN(13)

C   THE GLOBAL LOCATION OF SEGMENT CENTERS IS PLACED IN XYZCG FOR
C   SEGMENTS THAT WILL USE ELLIP IN COMPUTATION OF MASS AND
C   MOMENTS OF INERTIA.
XYZCG(1,3) = (DD(4) - SMW + DD(1) - DD(5))/2.
XYZCG(2,3) = DD(4)
XYZCG(3,3) = DD(2) - 9.*SMW/2.
XYZCG(8,3) = DD(29) - DD(31)/2. + DD(28)/PI2
XYZCG(11,3) = XYZCG(8,3)

RETURN
END
C---SUBROUTINE SEGMASS-----C
C   SEGMASS COMPUTES APPROXIMATE SEGMENT MASSES. WTCOR IS THEN COMPUTED C
C   TO ADJUST BODY DENSITY, DENS, SO THAT TOTAL BODY MASS AGREES C
C   WITH DD(0). SEGMENT MASSES ARE THEN RECOMPUTED USING WTCOR. C
C-----C

```

```

SUBROUTINE SEGMA5
EXTERNAL TORSO, FEET
COMMON /FLOAT/ PI,PI2,PI4,DENS,GRAV
COMMON /CYL/ ZEES(6:15),ZH(15),NSEG(15),CGZ(15),WTCCR
COMMON /JNTS/ RNJ(3,29)
COMMON /SGMNTS/ ABCN(15,3),RMN(15),PHI(45),XYCG(30),ZCG(15)
COMMON /DIMS/ DD(-1:31)
REAL AN(15),BN(15),CN(15)
EQUIVALENCE (AN,ABCN),(BN,ABCN(1,2)),(CN,ABCN(1,3))
SUMM=0.0

C POSITIONS 0 THRU 3 OF ZEES DEFINE THE VERTICAL LIMITS OF TORSO
C SEGMENTS. 10 THRU 11 DEFINE THE LIMITS OF THE FEET.
SMW = (DD(2) - DD(4))/10.
ZEES(0) = DD(1) - DD(5)
ZEES(1) = DD(4) - SMW
ZEES(2) = DD(4) + SMW
ZEES(3) = DD(2)
ZEES(11) = DD(29) + DD(28)/PI2
ZEES(10) = ZEES(11) - DD(31)
DO 5 I = 1,3
    CALL ELLIP (I,TORSO,RMN(I))
    ZCG(I) = CGZ(I) - ZCG(I)
5    SUMM = SUMM + RMN(I)
    CALL ELLIP (1,FEET,RMN(11))
    SUMM = SUMM + 2.*RMN(11)
    RMN(9) = RMN(11)
    ZCG(11) = CGZ(11) - ZCG(11)
    ZCG(8) = ZCG(11)
DO 7 I = 1,3
7    RNJ(3,I) = RNJ(3,I) + ZCG(I)
    RNJ(3,15) = ZCG(2) + RNJ(3,15)
    RNJ(3,16) = ZCG(3) + RNJ(3,16)
    RNJ(3,5) = ZCG(1) + RNJ(3,5)
    RNJ(3,8) = ZCG(1) + RNJ(3,8)
    RNJ(3,11) = RNJ(3,11) + ZCG(3)
    RNJ(3,13) = RNJ(3,13) + ZCG(3)
    RNJ(3,21) = RNJ(3,21) + ZCG(8)
    RNJ(3,24) = RNJ(3,24) + ZCG(11)
DO 10 I = 4,7
    RMN(I) = 4.0/3.0*PI*AN(I)*BN(I)*CN(I)*DENS
    SUMM = SUMM+RMN(I)
    IF (I.GT.5) THEN
        SUMM = SUMM + RMN(I)
        RMN(I+3) = RMN(I)
    ENDIF
10 CONTINUE
DO 15 I = 12,13
    RMN(I) = 4.0/3.0*PI*AN(I)*BN(I)*CN(I)*DENS
    SUMM = SUMM+2.*RMN(I)
15 RMN(I+2) = RMN(I)

C THE FOLLOWING ADJUSTS SEGMENT MASSES TO TOTAL BODY WEIGHT
C
C    *TCOR = DD(0)/SUMM/GRAV
DO 20 I=1,15
    RMN(I)=RMN(I)**TCOR
20 CONTINUE
RETURN
END

C--SUBROUTINE SGINER-----C
C    SGINER COMPUTES SEGMENT MOMENTS OF INERTIA. C
C-----C

```

```

SUBROUTINE SGINER
EXTERNAL TORSO, FEET
COMMON /FLOAT/ PI,PI2,PI4
COMMON /SGNNTS/ AN(15),BN(15),CN(15),RMN(15),PHI(3,15)

DO 5 I=1,3
5   CALL ELLPMI (I,TORSO,PHI(1,I))
DO 10 I=4,7
TEMP=RMN(I)/5.0
A2=AN(I)*AN(I)
B2=BN(I)*BN(I)
C2=CN(I)*CN(I)
PHI(1,I)=TEMP*(B2+C2)
PHI(2,I)=TEMP*(A2+C2)
PHI(3,I)=TEMP*(A2+B2)
IF (I.GT.5) THEN
DO 7 J = 1,3
7   PHI(J,I+3) = PHI(J,I)
ENDIF
10 CONTINUE
DO 20 I=12,13
TEMP=RMN(I)/5.0
A2=AN(I)*AN(I)
B2=BN(I)*BN(I)
C2=CN(I)*CN(I)
PHI(1,I)=TEMP*(B2+C2)
PHI(2,I)=TEMP*(A2+C2)
PHI(3,I)=TEMP*(A2+B2)
DO 15 J = 1,3
15  PHI(J,I+2) = PHI(J,I)
20 CONTINUE
CALL ELLPMI (11,FEET,PHI(1,11))
DO 25 J=1,3
25  PHI(J,8) = PHI(J,11)
RETURN
END

C-----SUBROUTINE ELLIP-----C
C ELLIP COMPUTES MASS AND CENTER OF GRAVITY LOCATION OF A RIGHT C
C ELLIPTICAL SOLID. THE PARAMETERS ARE: C
C ISEG--SPECIFIES SEGMENT BEING MODELLED BY RIGHT ELLIPTICAL SOLID C
C ABEVAL--SPECIFIES SUBROUTINE TO BE USED TO COMPUTE SEMIAXES OF THE C
C THE SOLID AT SPECIFIC Z HEIGHTS. C
C TMASS--RETURNS THE MASS COMPUTED FOR THE SOLID. C
C-----C

SUBROUTINE ELLIP (ISEG,ABEVAL,TMASS)
COMMON /CYL/ ZEES(6:15),ZH(15),NSEG(15),CGZ(15),JTCOR
COMMON /FLOAT/ PI,PI2,PI4,DENS,GRAV
REAL IXX,IXXP,IYY,IYYP,IZZ,IZZP
REAL MASS
REAL MI(3)
TMASSO=0.0
Z0 = ZEES(ISEG-1)
Z1 = ZEES(ISEG)
NSEG(ISEG)=0.0
10 NSEG(ISEG)=NSEG(ISEG)+10
TCGN=0.0
TMASS=C.0
ZH(ISEG)=(Z1-Z0)/FLOAT(NSEG(ISEG))
DO 100 I=1,NSEG(ISEG)
Z = Z0 + (FLOAT(I-1)+.5)*ZH(ISEG)
CALL ABEVAL(Z,A,B)

```

```

      MASS=PI*A*B*ZH(ISEG)*DENS
      CG=Z
      CGN=CG*MASS
      TMASS=TMASS+MASS
100   TCGN=TCGN+CGN
      TMASSN=TMASS
      IF (ABS(TMASSN-TMASSO)/TMASSN.GT.5.E-5) THEN
        TMASSO = TMASSN
        GOTO10
      ENDIF
      CGZ(ISEG)=TCGN/TMASS
      RETURN

C  ENTRY ELLPMI
C  ELLPMI COMPUTES MOMENTS OF INERTIA OF A RIGHT ELLIPTICAL SOLID, BASED
C  ON THE NUMERICAL INTEGRATION DETERMINED BY ELLIP. THE FIRST TWO
C  PARAMETERS ARE THE SAME AS THOSE USED BY ELLIP. THE THIRD, MI,
C  RETURNS THE MOMENTS OF INERTIA OF THE SOLID.

      ENTRY EL PMI (ISEG,ABEVAL,MI)
      DO 5 I=1,3
        MI(I)=0.0
        Z0 = ZEES(ISEG-1)
        DO 200 I=1,NSEG(ISEG)
          Z = Z0 + (FLOAT(I-1)+.5)*ZH(ISEG)
          CALL ABEVAL(Z,A,B)
          MASS=PI*A*B*ZH(ISEG)*DENS*WTCOR
          IXX=(MASS/12)*(3.0*B**2+ZH(ISEG)**2)
          IYY=(MASS/12)*(3.0*A**2+ZH(ISEG)**2)
          IZZ=(MASS/4.0)*(A**2+B**2)
          DIST=Z-CGZ(ISEG)
          IXXP=IXX+MASS*DIST**2
          IYYP=IYY+MASS*DIST**2
          IZZP=IZZ
          MI(1)=MI(1)+IXXP
          MI(2)=MI(2)+IYYP
          MI(3)=MI(3)+IZZP
200   Z=Z+ZH(ISEG)
      RETURN
      END

C-----SUBROUTINE TORSO-----C
C  TORSO COMPUTES SEMIAXIS VALUES FOR THE RIGHT ELLIPTICAL MODEL OF THE C
C  THREE TORSO SEGMENTS. THE PARAMETERS ARE THE FOLLOWING: C
C  Z--VERTICAL LOCATION AT WHICH THE SEMIAXES ARE TO BE COMPUTED C
C  X--RETURNS X SEMIAXIS C
C  Y--RETURNS Y SEMIAXIS C
C-----C

      SUBROUTINE TORSO (Z,X,Y)
      COMMON /DIMS/ D(-1:31)
      COMMON /FLOAT/ PI,PI2
      REAL H2,H3,H4,H5,H6

C  H2--TOP OF SOLID
C  H3--BREAK BETWEEN TOP SEMI-ELLIPSOID AND TOP FRUSTRUM
C  H4--BREAK BETWEEN TWO FRUSTRUM
C  H5--BREAK BETWEEN BOTTOM FRUSTRUM AND BOTTOM SEMI-ELLIPSOID
C  H6--BOTTOM OF SOLID

      H2=D(2)
      H3=D(3)
      H4=D(4)
      H5=(D(1)-D(5))*D(24)/PI2

```

```

M6=(D(1)-D(5))
IF (Z.LT.H4)THEN
  IF (Z.LT.H5)THEN
    IF (Z.LT.H6)STOP 'Z IS LESS THAN MIN.'
    Y= SQRT(1. - ((Z - H5)/D(24)/PI2)**2)
    X = D(15)/2.*Y
    Y = D(16)/2.*Y
  ELSE
    Y=(Z-D(4))/(H5-D(4))
    X = (Y*(D(15)-D(13)) +D(13))/2.
    Y = (Y*(D(16)-D(14)) +D(14))/2.
  END IF
ELSE
  IF(Z.LT.H3)THEN
    Y=(Z-D(3))/(D(4)-D(3))
    X= (Y*(D(13)-D(11))+D(11))/2.
    Y= (Y*(D(14)-D(12))+D(12))/2.
  ELSE
    IF (Z.GT.H2) STOP 'Z IS GREATER THAN MAX.'
    Y=SQRT(1. - ((Z - D(3))/(D(2) - D(3)) )**2)
    X= Y*D(11)/2.
    Y= Y*D(12)/2.
  END IF
END IF
END
C--SUBROUTINE FEET-----C
C FEET COMPUTES SEMIAXIS VALUES FOR THE RIGHT ELLIPTICAL MODEL OF THE C
C FEET. THE PARAMETERS ARE THE FOLLOWING: C
C Z--Z LOCATION (TOE TO WHEEL) AT WHICH SEMIAXES ARE TO BE COMPUTED C
C X--RETURNS X SEMIAXIS C
C Y--RETURNS Y SEMIAXIS C
C-----C

SUBROUTINE FEET (Z,X,Y)
COMMON /CYL/ ZEES(0:15),ZH(15),NSEG(15),CGZ(15),WTCOR
COMMON /DIMS/ DD(-1:31)
COMMON /FLOAT/ PI,PI2

C H2--TOP OF SOLID
C H1--BREAK BETWEEN ELLIPTICAL CYLINDER AND FRUSTRUM
C H0--BOTTOM OF SOLID

ANKR = DD(29)/PI2
H2 = DD(29) + ANKR
H1 = DD(29) - ANKR
H0 = H2 - DD(31)

IF (Z.GT.H1) THEN
  IF (Z.GT.H2) STOP 'Z VALUE TOO LARGE IN FEET'
  X = ANKR
  Y = ANKR
ELSE
  IF (Z.LT.H0) STOP 'Z VALUE TOO SMALL IN FEET'
  X = ANKR/(DD(31) - 2.*ANKR)*(Z - DD(29) + DD(31) - ANKR)
  Y = (ANKR - DD(30)/2.)/(DD(31) - 2.*ANKR)
  Y = Y*(Z - DD(29) + ANKR) + ANKR
ENDIF

RETURN
END
C--SUBROUTINE RESULTS-----C
C REGU15 WRITES OUT THE COMPUTED BODY DESCRIPTION DATA. C
C-----C

```

```

SUBROUTINE RESULTS (ISTRT)
COMMON /SGMNTS/ A(15),B(15),C(15),RMN(15),PHI(3,15),
3 XCG(15),YCG(15),ZCG(15)
COMMON /JNTS/ RNJ(3,14,2),JNT(14),YPRLL(14,6),IPIN(14)
COMMON /DIMS/ DD(-1:31)
COMMON /NAMES/ SUBTYP(4),SEGLAB(15),JNTLAB(14),PLTSYM(29),
5 DIMLAB(-1:31),TITLE,UNITS(3,-1:2)
COMMON /CYL/ ZEES(0:15),ZH(15),NSEG(15),CGZ(15),WTCOR
CHARACTER SUBTYP*20,SEGLAB*3,JNTLAB*2,PLTSYM*1,DIMLAB*24,TITLE*60
CHARACTER ANS*1,UNITS*6,LABL1(2)*6,LABL2(2)*12,LABL3(2)*2,
6 LABL4(2)*4,VARB*6
DATA LABL1,LABL2,LABL3,LABL4 /'WEIGHT','MASS','L3-SEC**2-IN',
8 'KG-M**2','IN','CM','LBS.','KG.'/,VARB/'OUTPUT'/
DATA IBET/201000000/, IA/240000000/

WRITE (9,11)
CALL ASKUN (VARB,UNITS(1,2),IUN,2)
CALL CNVRT (IUN)
IF (ISTRT.LT.0) WRITE (9,22) -1,DIMLAB(-1),DD(-1),UNITS(1,-1)
WRITE (9,22) 0,DIMLAB(0),DD(0),UNITS(IUN,0)
WRITE (9,22) (I,DIMLAB(I),DD(I),UNITS(IUN,1),I=1,31)
WRITE (9,66) WTCOR

WRITE (9,44) '1'//TITLE
WRITE(9,1170) LABL1(IUN),LABL2(IUN),LABL3(IUN),LABL3(IUN),
5 LABL4(IUN)
WRITE(9,1180) (I,SEGLAB(I),PLTSYM(I),RMN(I),(PHI(J,I),J=1,3),
3 A(I),B(I),C(I),XCG(I),YCG(I),ZCG(I),I=1,15)
WRITE(9,1190) LABL3(IUN),LABL3(IUN)
WRITE(9,1200) (I,JNTLAB(I),PLTSYM(I+15),JNT(I),IPIN(I),
8 ((RNJ(J,I,K),J=1,3),K=1,2),(YPRLL(I,J),J=1,6),I=1,14)

10 WRITE (5,33)
READ (7,44) ANS
IF (ANS.EQ.'Y') THEN
WRITE (3,77) TITLE(1:52)
WRITE(3,1300) (SEGLAB(I),PLTSYM(I),RMN(I),(PHI(J,I),J=1,3),
3 A(I),B(I),C(I),XCG(I),YCG(I),ZCG(I),IA+I*IBET,I=1,15)
C WRITE(3,1320) (JNTLAB(I),PLTSYM(I+15),JNT(I),IPIN(I),
5 ((RNJ(J,I,K),J=1,3),K=1,2),IA+I*IBET,
3 (YPRLL(I,J),J=1,6),I=1,14)
ELSE
IF (ANS.NE.'N') GOTO 10
ENDIF

20 WRITE (5,55)
READ (7,44) ANS
IF (ANS.EQ.'N') STOP 'FROM RESULTS'
IF (ANS.NE.'Y') GOTO 20
RETURN

11 FORMAT ('-COMPUTED BODY DIMENSIONS'/)
22 FORMAT (I10,A30,G15.4,A6)
33 FORMAT (' IS ATB MODEL FORMATTED OUTPUT DESIRED (Y/N) ?')
44 FORMAT (A)
55 FORMAT (' IS IT DESIRED TO PRODUCE ANOTHER BODY DESCRIPTION ',
5 'DATA SET (Y/N) ?')
56 FORMAT ('OWEIGHT CORRECTION FACTOR =',F10.3)
77 FORMAT (4X,'15',4X,'14',8X,A52,'CARD B.1')
1170 FORMAT( 1H0,"CRASH VICTIM PARAMETERS (3-D)"/1H0,33X,
1 25HSEGMENT MOMENT OF INERTIA,
2 19X,25HSEGMENT CONTACT ELLIPSOID/5X,7HSEGMENT,7X,A6

```

```

3,15X,'('A12,')',17X,10HSEMIAXIS ('A2,')',14X,'CENTER ('
4,A2,')',3X,12HNO. SYM PLOT,4X,'('A4,')',10X,1HX,10X,1HY,10X,
5HZ,12X,1HX,6X,1HY,6X,1HZ,12X,1HX,7X,1HY,6X,1HZ/1H )
1180 FORMAT ((3X,I2,2X,A4,A2,6X,F6.3,3X,3(4X,F7.5),5X,3(2X,F5.2),5X,3
1(3X,F5.2)))
1190 FORMAT(1H0,///3X,5HJOINT,16X,'LOCATION('A2,') - SEG(JNT)',5X,
1 'LOCATION('A2,') - SEG(J+1)',2X,'PRIN. AXIS(DEG) - SEG(JNT)',
2 ' PRIN. AXIS(DEG) - SEG(J+1)',2X,'J SYM PLOT JNT PIN',
3 4X,2(1X,'X',8X,'Y',8X,'Z',8X),2('YAW',5X,'PITCH',5X,'ROLL',6X)/)
1200 FORMAT ((I3,A4,A3,2X,I3,4(3F9.2,1X)))
1300 FORMAT(A4,A2,F6.3,3F6.4,6F6.3,6X,'CARD 8.2.',A1)
1320 FORMAT(A4,1X,A1,2I4,6F6.2,22X,'CARD 9.3.',A1/14X,6F6.2)
END
C--SUBROUTINE CNVRT-----C
C CNVRT CONVERTS ALL OUTPUT DATA TO THE UNITS SELECTED BY THE USER C
C-----C

SUBROUTINE CNVRT (IUN)
COMMON /SGPNTS/ ABC(15,3),RPN(15),PHI(3,15),XYZCG(15,3)
COMMON /JNTS/ RNJ(3,28)
COMMON /DIMS/ DD(-1:31)
REAL CONV(2,3)
DATA CONV /1.,2.54,32.17405,14.5939,12.,105.4034/

DO 100 I = 1,15
DO 10 J = 1,3
ABC(I,J) = ABC(I,J)*CONV(IUN,1)
XYZCG(I,J) = XYZCG(I,J)*CONV(IUN,1)
10 PHI(J,I) = PHI(J,I)/CONV(IUN,3)
100 RMN(I) = RMN(I)*CONV(IUN,2)

DO 200 I = 1,28
DO 200 J = 1,3
200 RNJ(J,I) = RNJ(J,I)*CONV(IUN,1)

IF (IUN.GY.1) THEN
DD(C) = DD(0)/CONV(1,2)*CONV(2,2)
DO 300 I=1,31
300 DD(I) = DD(I)*CONV(2,1)
ENDIF

RETURN
END

```


REFERENCES

- Bartz, John A., July 1971, "A Three-Dimensional Computer Simulation of a Motor Vehicle Crash Victim, Phase I - Development of the Computer Program," VJ-2979-V-1, Calspan Corporation, Buffalo, New York.
- Bartz, John A. and Charles R. Gianotti, January 1973, "A Computer Program to Generate Input Data Sets for Crash Victim Simulations," ZQ-5167-V-1, Calspan Corporation, Buffalo, New York.
- Baughman, L. Douglas, April 1982, "Segmentation and Analysis of Stereophotometric Body Surface Data," AFAMRL-TR-81-96, Air Force Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.
- Butler, F. E. and J. T. Fleck, May 1980, "Advanced Restraint System Modeling," AFAMRL-TR-80-14, Air Force Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.
- Chandler, R. F., C. E. Clauser, J. T. McConville, H. M. Reynolds, and J. W. Young, 1975, "Investigation of Inertial Properties of the Human Body," AMRL-TR-74-137, AD A-016485, Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.
- Clauser, Charles E., Pearl E. Tucker, John T. McConville, Edmund Churchill, Lloyd L. Laubach, Joan A. Reardon, April 1972, "Anthropometry of Air Force Women," AMRL-TR-70-5, Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.
- Fleck, J. T. and F. E. Butler, July 1975, "Development of an Improved Computer Model of the Human Body and Extremity Dynamics," AMRL-TR-75-14, Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.
- Fleck, J. T., F. E. Butler, and S. L. Vogel, April 1975, "An Improved Three-Dimensional Computer Simulation of Crash Victims," DOT-HS-801-507 through 510, National Technical Information Service, Springfield, Virginia.
- Grunhofer, H. J. and G. Kroh, 1975, "A Review of Anthropometric Data of German Air Force and United States Air Force Personnel 1967-1968," AGARD-AG-205, Advisory Group for Aerospace Research and Development, 7 Rue Ancelle 92200, Neuilly Sur Seine, France.
- Hanavan, Ernest P., October 1964, "A Mathematical Model of the Human Body," AMRL-TR-64-102, Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.

Leet, Duane G., September 1978, "MISEC2: An Interactive Fortran Program that Computes the Inertial Properties of a Homogeneous Right Elliptical Solid," UDR-TR-78-26, University of Dayton Research Institute, Dayton, Ohio.

McConville, John T., Thomas D. Churchill, Ints Kaleps, Charles E. Clauser, Jamie Cuzzi, December 1980, "Anthropometric Relationships of Body and Body Segment Moments of Inertia," AFAMRL-TR-80-119, Air Force Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio.

Segal, D. J., January 1971, "Revised Computer Simulation of the Automobile Crash Victim," VJ-2759-V-2, Calspan Corporation, Buffalo, New York.

Snyder, Richard G., Lawrence W. Schneider, Clyde L. Owings, Herbert M. Reynolds, D. Henry Golomb, M. Anthony Sckork, May 1977, "Anthropometry of Infants, Children, and Youths to Age 18 for Product Safety Design," UM-HSRI-77-17, Consumer Product Safety Commission, Bethesda, Maryland.

Walker, L. B., Jr., E. H. Harris, V. R. Pontius, 1973, "Mass, Volume, Center of Mass and Mass Moment of Inertia of Head and Neck of the Human Body," AD 762 581, Final Report, Department of the Navy, Office of Naval Research, Washington, D.C.